

DEC 4000 AXP Model 600 Series

Master Index

Order Number: EK-KN430-MI. A01

First Printing, January 1993

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may be used or copied only in accordance with the terms of such license.

No responsibility is assumed for the use or reliability of software on equipment that is not supplied by Digital Equipment Corporation or its affiliated companies.

© Digital Equipment Corporation 1993.

All Rights Reserved.

The postpaid Reader's Comments forms at the end of this document request your critical evaluation to assist in preparing future documentation.

The following are trademarks of Digital Equipment Corporation: Alpha AXP, AXP, CompacTape, DEC, DECchip, DECconnect, DECdirect, DECnet, DECserver, DEC VET, DESTA, MSCP, RRD40, RRD42, RZ, ThinWire, TMSCP, TU, TZ, UETP, VAX, VAXcluster, VAXsimPLUS, VMS, VMScluster, VT, the AXP logo, and the DIGITAL logo.

OSF/1 is a registered trademark of Open Software Foundation, Inc. UNIX is a registered trademark of UNIX System Laboratories, Inc.

S1749

This document is available on CD-ROM.

This document was prepared using VAX DOCUMENT, Version 2.1.

Preface

Purpose of This Index

The *Master Index* is intended to help you find information in the DEC 4000 AXP Customer Kit and the DEC 4000 AXP Service and Self-Maintenance Kit.

Who Should Use This Index

This index is for system managers and others who perform system management tasks; for Digital service representatives; for engineers who are designing equipment that interfaces to the DEC 4000 AXP system; and for general users of the system.

Structure of This Index

This index contains entries for the following documents. A key is used to designate each document.

- *DEC 4000 AXP Model 600 Owner's Guide*—OWNR
- *DEC 4000 AXP Model 600 Service Guide*—SVCE
- *DEC 4000 AXP Model 600 Technical Manual*—TECH

The master index also contains pointers to the following additional documents:

- *DEC 4000 AXP Model 600 Site Preparation*
- *DEC 4000 AXP Model 600 Quick Installation*
- *DEC 4000 AXP Model 600 Options Guide*

Finding the Documents and Courses You Need

On the front page of this guide, an “Information Map” shows you how the DEC 4000 AXP information products are organized. Documents can be ordered separately or as complete kits.

Two DEC 4000 AXP documentation kits are available: a Customer Kit and a Service and Self-Maintenance Kit. To order a kit, use the appropriate kit part number shown in Table 1 and 2. Order individual documents by the document’s part number.

The kit contents are as follows:

Table 1 Customer Documentation Kit: EK-KN430-KT

Document	Part Number
<i>DEC 4000 AXP Quick Installation</i>	EK-KN430-IN
<i>DEC 4000 AXP Information Map</i>	EK-KN430-IM
<i>DEC 4000 AXP Site Preparation Checklist</i>	EK-KN430-SP
<i>DEC 4000 AXP Owner’s Guide</i>	EK-KN430-OP

Table 2 Service and Self-Maintenance Kit: EK-KN430-DK

Document	Part Number
<i>DEC 4000 AXP Quick Installation</i>	EK-KN430-IN
<i>DEC 4000 AXP Information Map</i>	EK-KN430-IM
<i>DEC 4000 AXP Service Guide</i>	EK-KN430-SV
<i>DEC 4000 AXP Options Guide</i>	EK-KN430-OG
<i>DEC 4000 AXP IPB: Enclosure</i>	EK-EN430-IP
<i>DEC 4000 AXP IPB: Mass Storage</i>	EK-MS430-IP
<i>DEC 4000 AXP IPB: Pedestal System</i>	EK-SY430-IP
<i>DEC 4000 AXP Master Index</i>	EK-KN430-MI
<i>DEC 4000 AXP Technical Manual</i>	EK-KN430-TM
<i>DSSI VAXcluster Installation and Troubleshooting</i>	EK-410AA-MG

You may also wish to order related Alpha AXP or DEC 4000 AXP documents or take relevant courses. The following table lists some additional documents, periodicals, and courses.

Table 3 Related Documents and Courses

Document	Part Number
<i>Alpha AXP Systems Handbook</i> ¹	
<i>Systems and Options Catalog</i> ¹	
DEC 4000 AXP Information Sheet ¹	EC-F2006-41
<i>Digital's Customer Update</i> ¹	
<i>Digital Insight</i> ¹	
<i>OpenVMS Alpha V.1 Installation Manual</i>	AA-PQYSA-TE
<i>Guide to Installing DEC OSF/1</i>	AA-PS2DA-TE
Courses	Part Number
DEC 4000 AXP System Installation and Troubleshooting	EY-I090E-CO (Digital Services)
Alpha Architecture Concepts	EY-K725E-MT, -TK
Futurebus+ Concepts	EY-F479E-CO (Digital Services)

¹Contact your Digital sales representative for availability.

For complete ordering instructions, see “How to Order Documents and Courses,” at the back of this book.

For customer convenience, the *DEC 4000 AXP Model 600 Owner's Guide* is available on CD-ROM, as well as in hardcopy. The CD-ROM order number is QA-03XAA-H8.

To assist Digital service representatives, the complete DEC 4000 AXP information set is available through TIMA (Digital's Technical Information Management Architecture) as printable PostScript files. In addition, the *Service Guide* and *Owner's Guide* are available through TIMA in Bookreader format.

Index

A

- A32 Futurebus+ address space, *TECH*, 15-1
- A64 Futurebus+ address space, *TECH*, 15-2
- A-box control register, *TECH*, 4-23
- A-box IPRs, *TECH*, 4-19
- A-BOX_CTL, *TECH*, 4-23
- Acceptance testing, *SVCE*, 361
- Access doors, *TECH*, 1-5
- Accessories box, *OWNR*, 8-2
- AC circuit breaker, *OWNR*, 1-9
- AC power connector port, *TECH*, 1-48
- Adapters, mass storage, *OWNR*, 7-10
- ADDER, *TECH*, 18-47
- Address decoding
 - SCSI controller, *TECH*, 16-1
- Addresses
 - D-bus microcontroller, *TECH*, 1-43
 - I/O port to serial control bus, *TECH*, 1-43
 - memory module serial bus, *TECH*, 1-43
 - OCP serial bus, *TECH*, 1-43
 - PSC 8-bit register, *TECH*, 1-43
 - See Drive addresses
 - Ethernet
 - vterm 8-bit register, *TECH*, 1-43
 - 256X8 NVRAM, *TECH*, 1-43
- Address field, *TECH*, 19-11
 - for 1-MB cache, *TECH*, 19-11
 - for 4-MB cache, *TECH*, 19-11
- Addressing, *TECH*, 3-1
 - Lbus, *TECH*, 16-1
- Address mapping, *TECH*, 13-1
- Address space, *TECH*, 19-1
- Algorithms
 - bootstrap, *TECH*, 23-2
 - update vs. invalidate, *TECH*, 5-19
- ALLCLASS parameter, *OWNR*, 6-27;
SVCE, 667
- Allocation classes, changing, *OWNR*, 6-24
- alloc command, *TECH*, D-2
- Alpha AXP architecture, *TECH*, 3-1
 - See System architecture
- Alpha AXP chip
 - See DECchip 21064 microprocessor
- Alternate processor mode register, *TECH*, 4-24
- ALT_MODE, *TECH*, 4-24
- ANALYZE/ERROR command, *SVCE*, 398
- Antistatic wrist strap, *OWNR*, 8-6
- Arbitration signals, *TECH*, 19-9
- Architecture
 - See System architecture
- ASTER, *TECH*, 4-17
- ASTRR, *TECH*, 4-15
- Asynchronous system trap enable register, *TECH*, 4-17
- Asynchronous trap request register, *TECH*, 4-15
- ASYNC_RESET L, *TECH*, 19-17
- ASYNC_RESET_L, *TECH*, 21-5
- Autoboot, *OWNR*, 4-5
- AUTO_ACTION, *TECH*, 24-2
- auto_action environment variable
 - described, *OWNR*, 4-2
 - displaying current value, *OWNR*, 4-5
 - setting, *OWNR*, 4-6
 - settings, *OWNR*, 4-4

auto_action environment variable (cont'd)

uses of, *OWNR*, 4-5

Auxiliary serial line, *TECH*, 16-2

Auxiliary serial port, *TECH*, 16-2; *OWNR*, 2-2; *SVCE*, 691

changing baud rate setting, *OWNR*, 4-15

AUX_CTRL, *TECH*, 16-4

AUX_Data register, *TECH*, 16-4

Availability, system, *OWNR*, 6-5

B

BA640 enclosure

components, *SVCE*, 548

description, *TECH*, 1-5

front and rear, *SVCE*, 555

Backplane

diagram, *SVCE*, 554

removal and replacement, *SVCE*, 535

Backplane assembly, *TECH*, 1-10

Backup cache, *TECH*, 5-1

access time, *TECH*, 5-17

behavior on tag control parity error, *TECH*, 9-7

behavior on tag parity errors, *TECH*, 9-7

initialization, *TECH*, 11-1

memory devices, *TECH*, 1-21

Backup cache control register, *TECH*, 5-3

Backup cache correctable error address register, *TECH*, 5-11

Backup cache correctable error register, *TECH*, 5-8

Backup cache tag register, *TECH*, 4-36

Backup cache uncorrectable error address register, *TECH*, 5-15

Backup cache uncorrectable error register, *TECH*, 5-12

BARRIER, *TECH*, 7-1

BARRIER transaction, *TECH*, 7-6

Baud rate, changing, *OWNR*, 8-8

on auxiliary serial port, *OWNR*, 4-15

temporarily, on console terminal port, *OWNR*, 4-15

Baud rates, *TECH*, 1-9

auxiliary serial port, *SVCE*, 691

console serial port, *SVCE*, 686

Bcache

See Backup cache

BCCEA, *TECH*, 5-11

BCREQ L, *TECH*, 19-10

BC_TAG, *TECH*, 4-36

bin command, *TECH*, D-3

BIP flag, *TECH*, 24-2

BIU, *TECH*, 19-1

BIU_ADDR, *TECH*, 4-32

BIU_CTL, *TECH*, 4-26

BIU_STAT, *TECH*, 4-31

Block count, *TECH*, 23-5

Block diagrams

I/O expansion area, *TECH*, 1-37

I/O module, *TECH*, 1-22

initialization, *TECH*, 21-2

KN430 CPU subsystem, *TECH*, 1-15

KN430 processor module, *TECH*, 1-18

mass storage area, *TECH*, 1-34

operator control panel, *TECH*, 1-7

power supply, *TECH*, 1-39

Boot block calling interface, *TECH*, 23-4

boot command, *TECH*, D-4; *OWNR*, 3-5

bootdef_dev environment variable

described, *OWNR*, 4-2

disabling, *OWNR*, 4-9

displaying current value, *OWNR*, 4-7

setting, *OWNR*, 4-7

Boot devices, *TECH*, 23-5; *SVCE*, 164

changing default, *OWNR*, 4-7, 4-9

disabling default, *OWNR*, 4-9

displaying default value, *OWNR*, 4-7

Boot diagnostic flow, *SVCE*, 25

Boot failures, troubleshooting, *SVCE*, 18

Boot flags

default value, *OWNR*, 4-10

defined, *OWNR*, 4-10

displaying current value, *OWNR*, 4-12

setting, *OWNR*, 4-13

when to change, *OWNR*, 4-12

- Booting
 - BOOTP, *TECH*, 23-8
 - disk, *TECH*, 23-6
 - Ethernet, *TECH*, 23-6
 - MOP, *TECH*, 23-7
 - tape, *TECH*, 23-6
 - Booting system software screen, *OWNR*, 1-16
 - Boot message register format, *TECH*, 17-26
 - Boot parameters, *TECH*, 23-5
 - BOOTP booting, *TECH*, 23-8
 - BOOTP bootstrap, *TECH*, 23-10
 - Boot procedure, *OWNR*, 1-15
 - Boot processor, *TECH*, 23-2
 - Boot sequence, *SVCE*, 146
 - cold bootstrap, *SVCE*, 150
 - loading software, *SVCE*, 154
 - multiprocessor bootstrap, *SVCE*, 162
 - warm bootstrap, *SVCE*, 158
 - Bootstrap, *TECH*, 23-2
 - BOOTP, *TECH*, 23-10
 - cold start flag, *TECH*, 23-2
 - Bootstrap in progress flag, *TECH*, 23-2
 - boot_osflags environment variable
 - default value, *OWNR*, 4-10
 - described, *OWNR*, 4-2
 - displaying current value, *OWNR*, 4-12
 - setting, *OWNR*, 4-13
 - when to change, *OWNR*, 4-12
 - Bus
 - Futurebus+, *TECH*, 1-36
 - secondary, *TECH*, 1-33
 - serial control, *SVCE*, 581
 - system, *TECH*, 1-29; *SVCE*, 559
 - Buses, storage
 - extending, *OWNR*, 6-18
 - extending fast SCSI, *OWNR*, 6-18
 - named by compartment, *OWNR*, 6-8
 - terminating and extending, *OWNR*, 6-20
 - Bus expansion ports
 - described, *OWNR*, 6-18
 - location of, *OWNR*, 6-19
 - Bus interface control unit register, *TECH*, 4-26
 - Bus interface unit, *TECH*, 19-1
 - Bus interface unit address register, *TECH*, 4-32
 - Bus interface unit status register, *TECH*, 4-31
 - Bus master
 - serial control bus, *TECH*, 1-43
 - Byte, *TECH*, 3-1
 - Byte offset
 - as address argument, *TECH*, 25-8
 - Byte stream, *TECH*, 25-7
 - See device*
 - Byte swapping
 - using the eval command (example), *TECH*, 25-15
- ## C
-
- C³ revision register, *TECH*, 6-18
 - Cable guide, location, *OWNR*, 1-5
 - Cache block merge buffer, *TECH*, 5-17
 - Cache block prefetch, lack of, *TECH*, 5-22
 - Cache invalidate management, *TECH*, 8-1
 - Cache line buffers, *TECH*, 1-22
 - Cache line format, *TECH*, 19-3
 - Cache protocol, *TECH*, 19-3
 - CAD<127:0>, *TECH*, 19-10
 - Caddy
 - See Compact disc caddy*
 - CAD parity coverage, *TECH*, 19-13
 - CA L, *TECH*, 19-14
 - Callbacks, *TECH*, 23-3
 - Card cage
 - contents, *OWNR*, 6-6
 - lights, *OWNR*, 1-8
 - location, *OWNR*, 1-7
 - Cartridges
 - See CompactTape cartridges;*
 - CompactTape II cartridges;
 - CompactTape III cartridges; Tape drive media

cat command, *TECH*, D-6
 cat el command, *SVCE*, 100
 cbcc command, *TECH*, D-7
 CC, *TECH*, 4-25
 CCITT V.10, *TECH*, 16-2
 CCITT V.28, *TECH*, 16-2
 CC_CTL, *TECH*, 4-25
 CDIRTY L, *TECH*, 19-15
 cdp command, *TECH*, D-9; *OWNR*, 3-7,
 6-26; *SVCE*, 656
 CD register, *TECH*, 16-5
 Central processing unit
 See CPU
 CERR1, *TECH*, 13-11
 CERR2, *TECH*, 13-17
 CERR3, *TECH*, 13-18
 CHALT L, *TECH*, 19-18
 Characters, control, supported in console
 mode, *OWNR*, 2-8
 Characters, keyboard, supported in console
 mode, *OWNR*, 2-6, 2-8
 check command, *TECH*, D-11
 Checksum, *TECH*, 23-5
 Chips
 85C30, *TECH*, 16-2
 accessing internal registers, *TECH*,
 16-3
 87C652
 startup, *TECH*, 21-6
 system bus interface, *TECH*, 6-1
 chmod command, *TECH*, D-12
 chown command, *TECH*, D-13
 CID<2:0>, *TECH*, 19-13
 CINT_TIM, *TECH*, 19-17
 CIRQ L<1:0>, *TECH*, 19-17
 clear command, *TECH*, D-14
 clear_mop_counter command, *SVCE*, 261
 Clock frequencies
 151.51 Mhz, *TECH*, 1-33
 Clocking signals, *TECH*, 19-18
 Clocks, *TECH*, 1-33
 differential clock signals, *TECH*, 1-33
 ECL, *TECH*, 1-33
 generation, *TECH*, 1-33
 interval timer interrupt, *TECH*, 1-31

Clocks (cont'd)

 PECL, *TECH*, 1-21
 power/detect, *TECH*, 1-21
 system bus, *TECH*, 1-21, 6-22
 TOY registers, *TECH*, 1-25
 cmp command, *TECH*, D-15
 Cold bootstrap, *SVCE*, 150
 Command address cycle format, *TECH*,
 19-6
 Command and address format, *TECH*, 19-9
 Command CID assignments, *TECH*, 19-13
 Commander, *TECH*, 1-29, 19-19
 Commands
 See also Console commands
 alloc, *TECH*, D-2
 bin, *TECH*, D-3
 boot, *TECH*, D-4
 cat, *TECH*, D-6
 cbcc, *TECH*, D-7
 cdp, *TECH*, D-9
 check, *TECH*, D-11
 chmod, *TECH*, D-12
 chown, *TECH*, D-13
 clear, *TECH*, D-14
 cmp, *TECH*, D-15
 continue, *TECH*, D-17
 crc, *TECH*, D-18
 date, *TECH*, D-19
 deposit, *TECH*, D-20
 diagnostic, summarized, *SVCE*, 281
 diagnostic-related, *SVCE*, 176
 dynamic, *TECH*, D-23
 echo, *TECH*, D-25
 edit, *TECH*, D-26
 eval, *TECH*, D-29
 examine, *TECH*, D-31
 exer, *TECH*, D-34
 exer_read, *TECH*, D-40
 exer_write, *TECH*, D-41
 exit, *TECH*, D-42
 fbus_diag, *TECH*, D-43
 fbus_sizer, *TECH*, D-45
 find_field, *TECH*, D-46
 firmware console, functions of, *SVCE*, 41
 free, *TECH*, D-47

Commands (cont'd)

grep, *TECH*, D-48
hd, *TECH*, D-50
help, *TECH*, D-51
initialize, *TECH*, D-53
io_diag, *TECH*, D-54
kill, *TECH*, D-55
kill_diags, *TECH*, D-56
line, *TECH*, D-57
ls, *TECH*, D-58
memexer, *TECH*, D-59
memexer_mp, *TECH*, D-60
memtest, *TECH*, D-61
net, *TECH*, D-64
nettest, *TECH*, D-67
ps, *TECH*, D-70
psc, *TECH*, D-71
rm, *TECH*, D-72
sa, *TECH*, D-73
semaphore, *TECH*, D-74
set, *TECH*, D-75, D-77
sh, *TECH*, D-79
show, *TECH*, D-80, D-83, D-84, D-85,
D-87, D-89, D-90, D-91, D-92
show_status, *TECH*, D-93
sleep, *TECH*, D-94
sort, *TECH*, D-95
sp, *TECH*, D-96
start, *TECH*, D-97
stop, *TECH*, D-98
sw, *TECH*, D-99
test, *TECH*, D-100
to examine system configuration, *SVCE*,
612
to perform extended testing and
exercising, *SVCE*, 174
to report status and errors, *SVCE*, 173
to set and examine DSSI device
parameters, *SVCE*, 647
tr, *TECH*, D-102
uniq, *TECH*, D-103
update, *TECH*, D-104
used as abbreviations, *TECH*, 25-8
wc, *TECH*, D-106

CompacTape cartridges

compatibility with TZ30, *OWNR*, 5-29
compatibility with TZ85, *OWNR*, 5-22
handling and storage, *OWNR*, 5-39
inserting into TZ30, *OWNR*, 5-32
inserting into TZ85, *OWNR*, 5-24
label position, *OWNR*, 5-38
removing from TZ30, *OWNR*, 5-34
removing from TZ85, *OWNR*, 5-26

CompacTape II cartridges

compatibility with TZ30, *OWNR*, 5-29
compatibility with TZ85, *OWNR*, 5-22
inserting into TZ30, *OWNR*, 5-32
inserting into TZ85, *OWNR*, 5-24
label position, *OWNR*, 5-38
removing from TZ30, *OWNR*, 5-34
removing from TZ85, *OWNR*, 5-26

CompacTape III cartridges

compatibility with TZ30, *OWNR*, 5-29
compatibility with TZ85, *OWNR*, 5-22
inserting into TZ85, *OWNR*, 5-24
label position, *OWNR*, 5-38
removing from TZ85, *OWNR*, 5-26

Compact disc caddy

handling and storage, *OWNR*, 5-38
loading a disc into, *OWNR*, 5-14

Compact disc drive, supported by UETP,
SVCE, 333

Compact disc drives

See also RRD42 drives
operating, *OWNR*, 5-12

Compatibility, system, with OpenVMS AXP
and DEC OSF/1 AXP, *OWNR*, 7-3

Conditional branching

in if, while, until loops, *TECH*, 25-15

Configuration, *OWNR*, 6-2

DSSI VMScluster, *OWNR*, 6-4
dual CPU, *OWNR*, 6-4
errors, *SVCE*, 288
examining, *SVCE*, 612
of environment variables, *SVCE*, 635

Configuration rules

fixed-media, *SVCE*, 602
removable-media, *SVCE*, 606

Connectors

- CPU clock, *TECH*, 19–8
- memory, *TECH*, 1–29

Console

- diagnostic flow, *SVCE*, 23
- firmware commands, *SVCE*, 41
- preparing for BOOTP boot, *TECH*, 23–8
- reporting failures, *SVCE*, 18
- services, *TECH*, 1–46
- troubleshooting, *SVCE*, 18

Console command option -n

- specifying repeat count, *TECH*, 25–9

Console commands

- See also specific commands
- cdp, *SVCE*, 656
- clear_mop_counter, *SVCE*, 261
- contrasted with VAX, *TECH*, 25–4
- contrasted with VAX commands, *OWNR*, 3–3
- diagnostic and related, summarized, *SVCE*, 281
- displaying, *OWNR*, 3–3
- editing, *OWNR*, 2–6
- entering, *OWNR*, 3–3
- exer_read, *SVCE*, 226
- exer_write, *SVCE*, 235
- extending to a second line, *OWNR*, 2–6
- fbus_diag, *SVCE*, 245
- frequently used (table), *TECH*, 25–4
- kill, *SVCE*, 274
- kill_diags, *SVCE*, 274
- levels, *OWNR*, 3–1
- list of, *OWNR*, 3–1
- memexer, *SVCE*, 214
- memexer_mp, *SVCE*, 220
- recalling, *OWNR*, 2–6
- set bootdef_dev, *SVCE*, 645
- set boot_osflags, *SVCE*, 645
- set envvar, *SVCE*, 638
- set host -dup, *SVCE*, 287
- show auto_action, *SVCE*, 645
- show config, *SVCE*, 614
- show device, *SVCE*, 619
- show device du pu, *SVCE*, 648
- show envvar, *SVCE*, 638

Console commands (cont'd)

- show error, *SVCE*, 205
- show fru, *SVCE*, 185
- show memory, *SVCE*, 630
- show_mop_counter, *SVCE*, 256
- show_status, *SVCE*, 196
- summarized, *TECH*, 25–18
- test, *SVCE*, 177

Console diagnostics

- structure of, *TECH*, 1–45

Console EEPROM, *TECH*, 1–46

Console event log, *SVCE*, 100

Console mode

- See also Console program
- control characters supported in, *OWNR*, 2–8
- defined, *OWNR*, 1–10
- invoking, *OWNR*, 1–18
- invoking from across the Ethernet, *OWNR*, 2–5
- invoking from a powered-down state, *OWNR*, 2–4
- invoking from a remote device, *OWNR*, 2–5
- keyboard characters, supported, *OWNR*, 2–6
- online help in, *OWNR*, 3–3
- prompt, *OWNR*, 2–6
- uses of, *OWNR*, 2–1

Console port, testing, *SVCE*, 267

Console port baud rate, *SVCE*, 685

Console program, *OWNR*, 2–2

Console prompt, *OWNR*, 2–6

Console serial line, *TECH*, 16–2

Console serial port, *SVCE*, 686

Console serial ports, *TECH*, 16–2

Console shell operators (table), *TECH*, 25–16

Console subsystem

- components, *OWNR*, 2–2, 2–3
- finding additional information about, *OWNR*, 3–25

Console tasks

- examining and depositing stuff, *TECH*, 25–7

Console tasks (cont'd)
 examining registers, *TECH*, 25-9
 Console terminal, *OWNR*, 2-2
 remote, *OWNR*, 2-2, 2-5
 Console terminal port, *OWNR*, 2-2
 changing baud rate setting, *OWNR*, 4-15
 continue command, *TECH*, D-17; *OWNR*,
 3-10
 Continuous system bus transactions, *TECH*,
 1-30
 Control characters, *OWNR*, 2-8
 Controls, accessing, *OWNR*, 1-2
 Control store, *TECH*, 5-1
 CON_CTRL, *TECH*, 16-5
 CPU 2ID L, *TECH*, 19-18
 CPU clock connector
 initialization signal, *TECH*, 19-17
 CPUG L, *TECH*, 19-10
 CPU LEDs
 and CRESET L, *TECH*, 21-4
 CPU module, *SVCE*, 562
 adapter, *OWNR*, 7-10
 benefits of two, *OWNR*, 6-4
 DEC 4000 AXP design, *OWNR*, 7-2
 described, *OWNR*, 7-6
 location of, *OWNR*, 1-7
 removal and replacement, *SVCE*, 525
 subsystems, *TECH*, 2-2
 transactions, *TECH*, 7-1
 CPUREQ L, *TECH*, 19-10
 CPU specific buffer, *TECH*, 5-17
 CPU subsystem components, *OWNR*, 7-6
 CPU system bus register definitions, *TECH*,
 6-1
 Crash dumps, *SVCE*, 47
 crc command, *TECH*, D-18
 Creating scripts
 using the output creation operator (>),
 TECH, 25-13
 CRESET L, *TECH*, 6-21, 19-18
 and the system bus clock, *TECH*, 6-22
 CRESET_L, *TECH*, 21-5
 CSHARED L, *TECH*, 19-15

 CSR0, *TECH*, 5-3
 CSR1, *TECH*, 5-8
 CSR10, *TECH*, 6-13
 CSR11, *TECH*, 6-14
 CSR2, *TECH*, 5-11
 CSR3, *TECH*, 5-12
 CSR4, *TECH*, 5-15
 CSR5, *TECH*, 5-20
 CSR6, *TECH*, 6-1
 CSR7, *TECH*, 6-4
 CSR8, *TECH*, 6-10
 CSR9, *TECH*, 6-11
 CSR map, *TECH*, 17-1
 CSR read time, *TECH*, 1-33
 CSTALL0 L and CSTALL1 L, *TECH*, 19-14
 CSYS_EVENT L, *TECH*, 19-17
 CTEST0, *TECH*, 18-24
 CTEST1, *TECH*, 18-25
 CTEST2, *TECH*, 18-26
 CTEST3, *TECH*, 18-27
 CTEST4, *TECH*, 18-28
 CTEST5, *TECH*, 18-29
 CTEST6, *TECH*, 18-31
 CTEST7, *TECH*, 18-32
 CTEST8, *TECH*, 18-37
 Ctrl/A, function in console mode, *OWNR*,
 2-8
 Ctrl/C, function in console mode, *OWNR*,
 2-8
 Ctrl/E, function in console mode, *OWNR*,
 2-8
 Ctrl/H, function in console mode, *OWNR*,
 2-8
 Ctrl/O, function in console mode, *OWNR*,
 2-8
 Ctrl/P, function in console mode, *OWNR*,
 2-8
 Ctrl/Q, function in console mode, *OWNR*,
 2-8
 Ctrl/R, function in console mode, *OWNR*,
 2-8
 Ctrl/S, function in console mode, *OWNR*,
 2-8

Ctrl/U, function in console mode, *OWNR*, 2-8
Ctrl/X, function in console mode, *OWNR*, 2-8
Ctrl/Z, function in console mode, *OWNR*, 2-8
CUCERR L, *TECH*, 19-17
CXACK L, *TECH*, 19-14
Cycle counter control register, *TECH*, 4-25
Cycle counter register, *TECH*, 4-25
C_ERR, *TECH*, 14-2
C_ERR L, *TECH*, 19-16

D

Data cache status register, *TECH*, 4-29
Data delivered to I/O is known bad error, *SVCE*, 450
Data integrity, *TECH*, 5-22
Data store, *TECH*, 5-2
Data translation buffer ASM register, *TECH*, 4-22
Data translation buffer invalidate signal register, *TECH*, 4-22
Data translation buffer page table entry register, *TECH*, 4-19
Data translation buffer page table entry temporary register, *TECH*, 4-20
Data translation buffer zap register, *TECH*, 4-22
Data types, *TECH*, 3-1
Data width options, *TECH*, 25-8
Data wrap, *TECH*, 1-30
Data write, *TECH*, 1-43
Date, setting, *OWNR*, 3-11
date command, *TECH*, D-19; *OWNR*, 3-11
DBC, *TECH*, 18-39
D-bus, *TECH*, 6-19
DC3, *TECH*, 1-42
DC5, *TECH*, 1-42
DCMD, *TECH*, 18-39
DCNTL, *TECH*, 18-45
DC on/off switch, *TECH*, 1-8; *OWNR*, 1-6
DC_STAT, *TECH*, 4-29
DDS tapes
 and TLZ06 drive, *OWNR*, 5-16
 inserting into TLZ06, *OWNR*, 5-18
 label position, *OWNR*, 5-38
 removing from TLZ06, *OWNR*, 5-18
DECchip 21064 microprocessor, *OWNR*, 7-2; *SVCE*, 566
A-box, *TECH*, 4-19
cycle types, *TECH*, 7-1
features, *TECH*, 4-1
startup, *TECH*, 21-6
supported data types, *TECH*, 4-1
transactions
 allocate-invalid, *TECH*, 7-8
 BARRIER, *TECH*, 7-6
 cacheable, *TECH*, 7-7
 fast external cache read hit, *TECH*, 7-2
 fast external cache write hit, *TECH*, 7-3
 FETCH, *TECH*, 7-7
 FETCHM, *TECH*, 7-7
 LDxL, *TECH*, 7-6
 non-cacheable, *TECH*, 7-7
 READ_BLOCK, *TECH*, 7-4
 STxC, *TECH*, 7-6
 WRITE_BLOCK, *TECH*, 7-5
DECchip™
 startup code, *TECH*, 1-45
DECnet protocol, *OWNR*, 2-5
DECnet-VAX, preparing for UETP, *SVCE*, 339
DEC OSF/1 AXP operating system
 booting software on, *OWNR*, 1-16
 compatibility with DEC 4000 AXP, *OWNR*, 7-3
 shutdown, *OWNR*, 1-17
DEC VET
 operating system exerciser, *SVCE*, 45
 tests, *SVCE*, 299
Default boot device
 changing, *OWNR*, 4-7, 4-9
 disabling, *OWNR*, 4-9
 displaying, *OWNR*, 4-7

- Default boot device (cont'd)
 - setting, *OWNR*, 4-9
- Default startup action, setting, *OWNR*, 4-6
- deposit command, *TECH*, D-20
 - accessing physical memory (example), *TECH*, 25-8
- Descriptor lists, *TECH*, 17-28
- Descriptors and buffers format, *TECH*, 17-28
- Device, *TECH*, 25-7
- Device naming convention, *SVCE*, 619
- Devices
 - changing drive ID plugs, *OWNR*, 6-23
 - changing DSSI device parameters, *OWNR*, 6-24
 - connecting external, *OWNR*, 6-18
 - displaying status of in console mode, *OWNR*, 6-13
 - platform-specific (list), *TECH*, 25-8
- DFIFO, *TECH*, 18-33
- DIAGCSR, *TECH*, 13-20
- Diagnostic flows
 - boot problems, *SVCE*, 25
 - console, *SVCE*, 23
 - errors reported by operating system, *SVCE*, 26
 - power, *SVCE*, 21
 - problems reported by console, *SVCE*, 24
- Diagnostic mode address registers, *TECH*, 13-5
- Diagnostic mode data registers, *TECH*, 13-4
- Diagnostics
 - command summary, *SVCE*, 281
 - command to terminate, *SVCE*, 176, 274
 - DSSI storage devices, *SVCE*, 284
 - power-on, *SVCE*, 62
 - related commands, *SVCE*, 176
 - related commands, summarized, *SVCE*, 281
 - relationship to UETP, *SVCE*, 347
 - ROM-based, *SVCE*, 36, 168
 - showing status of, *SVCE*, 196
 - structure of, *TECH*, 1-45
 - system LEDs, *SVCE*, 62
- Diagnostic tools, *SVCE*, 18
- DIEN, *TECH*, 18-43
- DIRECT local program, *SVCE*, 293
- Disk drives
 - See also RRD42 drives
 - described, *OWNR*, 5-5
 - mounting, *OWNR*, 5-2
 - operating, *OWNR*, 5-5
- Disk power source voltages, *TECH*, 1-34
- Disks
 - testing reads, *SVCE*, 226
 - testing writes, *SVCE*, 235
- DKUTIL local program, *SVCE*, 293
- DMA watchdog timer register, *TECH*, 18-44
- DMODE, *TECH*, 18-42
- DNA CSMA/CD counters and events support, *TECH*, 17-51
- DNAD, *TECH*, 18-40
- Documentation, *OWNR*, 7-11; *SVCE*, 53
 - See also the *DEC 4000 Information Map* for configuration information, *OWNR*, 6-33
 - for console commands, *OWNR*, 3-25
 - for maintaining the system, *OWNR*, 8-10
 - for mass storage devices, *OWNR*, 5-42
 - for preparing the system for use, *OWNR*, 1-23
- Documentation conventions, *TECH*, xxxii
- Doors, system
 - opening, *OWNR*, 1-4
 - removing, *OWNR*, 8-4
 - unlocking, *OWNR*, 1-4
- Drive
 - error conditions, *SVCE*, 285
 - removal and replacement, *SVCE*, 489, 493, 497, 501, 504
- Drive addresses, determining, *OWNR*, 6-8
- Drive ID plugs
 - changing, *OWNR*, 6-23
 - function, *OWNR*, 6-8
 - using to color-code drives, *OWNR*, 6-8
 - when to change, *OWNR*, 6-22
- Driver initialization, *TECH*, 21-15

Drivers

- as access mechanisms, *TECH*, 25-7
- for Alpha AXP devices (list), *TECH*, 25-7

Drives

- See Mass storage devices; Tape drives;
Disk drives

- DRVEXR local program, *SVCE*, 293
- DRVTST local program, *SVCE*, 293
- DSA, *TECH*, 18-23
- DSP, *TECH*, 18-40
- DSPS, *TECH*, 18-41
- DSSI 3.5-inch disk drive
 - removal and replacement, *SVCE*, 501
- DSSI 5.25-inch disk drive
 - removal and replacement, *SVCE*, 504
- DSSI adapters, function of, *OWNR*, 7-10
- DSSI buses, terminating and extending, *OWNR*, 6-20
- DSSI device allocation classes, changing, *OWNR*, 6-24
- DSSI device internal tests, *SVCE*, 284
- DSSI device parameters
 - defined, *SVCE*, 664
 - function of, *SVCE*, 664
 - list of, *SVCE*, 664
 - modifying, *SVCE*, 656
 - need to modify parameters for, *SVCE*, 679
 - setting and showing, *SVCE*, 646
 - use by OpenVMS AXP, *SVCE*, 674
- DSSI devices
 - changing allocation classes for, *OWNR*, 6-24
 - cluster capability, *OWNR*, 6-4
 - errors, *SVCE*, 288
 - local programs, *SVCE*, 292
- DSSI ID plugs, *OWNR*, 6-8
 - See also Drive ID plugs
- DSSI parameters, *OWNR*, 6-26
- DSSI storageless tray assembly
 - removal and replacement, *SVCE*, 506
- DSSI VMScluster configurations, *OWNR*, 6-4

- DSTAT, *TECH*, 18-17
- DTBASM, *TECH*, 4-22
- DTBIS, *TECH*, 4-22
- DTBZAP, *TECH*, 4-22
- DTB_PTE, *TECH*, 4-19
- DTB_PTE_TEMP, *TECH*, 4-20
- Dual CPU systems, *OWNR*, 6-4
- DUP driver utility, *OWNR*, 6-26
- Duplicate primary data cache tag store, *TECH*, 5-18
- Duplicate tag error register, *TECH*, 5-20
- Duplicate tag store initialization, *TECH*, 11-3
- DUP server utility, *SVCE*, 664
- DWT, *TECH*, 18-45
- DWT register, *TECH*, 18-44
- dynamic command, *TECH*, D-23
- D_floating, *TECH*, 3-5

E

- ECHADR<15:0>, *TECH*, 19-11
- echo command, *TECH*, D-25
- ECL clock, *TECH*, 1-33
- EDC
 - See Error Detection and Correction
- edit command, *TECH*, D-26; *SVCE*, 120
- EEPROM, *TECH*, 16-2
 - command to report errors, *SVCE*, 205
 - console, *TECH*, 1-46
 - for serial control bus, *TECH*, 1-47
 - serial control bus interaction, *SVCE*, 585
 - write cycle time, *TECH*, 1-43
- EIA 423, *TECH*, 16-2
- Environment variables, *TECH*, 23-2
 - configuring, *SVCE*, 635
 - defined, *OWNR*, 4-1
 - described, *OWNR*, 4-2
 - displaying current status, *OWNR*, 4-2
 - preset values, *OWNR*, 4-2
 - setting and examining, *SVCE*, 635
 - setting before booting, *OWNR*, 1-14, 4-2
 - tasks after setting, *OWNR*, 4-19
 - tasks before setting, *OWNR*, 4-4

ERASE local program, *SVCE*, 293

ERF
 interpreting system faults with, *SVCE*, 411

ERF-generated error log, sample of, *SVCE*, 469

ERF/USERF error log format, *SVCE*, 389

Error detection and correction, *TECH*, 4–37

Error field bit definitions, *SVCE*, 415

Error formatters
 ERF, *SVCE*, 395
 USERF, *SVCE*, 395

Error handling, *SVCE*, 34

Error log
 ERF sample, *SVCE*, 469
 USERF sample, *SVCE*, 473

Error log format, *SVCE*, 391

Error logging, *SVCE*, 34
 event log entry format, *SVCE*, 389

Error logging EEPROM, *TECH*, 6–23

Error logs
 error field bit definitions for, *SVCE*, 415
 storage device generated, *SVCE*, 394

Error log translation
 DEC OSF/1, *SVCE*, 405
 OpenVMS AXP, *SVCE*, 398

Error Log Utility
 relationship to UETP, *SVCE*, 314, 349

Error report formatter (ERF), *SVCE*, 34

Errors
 backup cache tag control parity, *TECH*, 9–7
 backup cache uncorrectable, *SVCE*, 444
 bcache data single bit EDC, *TECH*, 9–7
 bcache data uncorrectable EDC, *TECH*, 9–7
 bcache single bit EDC, *TECH*, 9–15
 bcache tag or tag control parity, *TECH*, 9–8
 bcache tag parity, *TECH*, 9–15
 commands to report, *SVCE*, 185, 205
 configuration, *SVCE*, 288
 current CPU BCTC parity error processor detected, *TECH*, 9–7

Errors (cont'd)
 data delivered to I/O is known bad, *SVCE*, 450
 DECchip 21064 microprocessor
 data bus uncorrectable EDC, *TECH*, 9–8
 DECchip 21064 microprocessor
 data bus single bit EDC, *TECH*, 9–8
 EDC, *TECH*, 4–29
 EDC uncorrectable, *TECH*, 9–9
 Futurebus+ DMA parity error, *SVCE*, 455
 Futurebus+ mailbox access parity error, *SVCE*, 459
 handled by POST, *SVCE*, 285
 hardware 0, *TECH*, 9–15
 hardware interrupt, *TECH*, 14–2
 interpreting UETP failures, *SVCE*, 347
 invalidate system bus address, *TECH*, 9–9
 miscellaneous CPU, *TECH*, 9–9
 multievent analysis of, *SVCE*, 463
 parity, *TECH*, 4–29
 system bus parity, *TECH*, 9–9, 9–16
 system bus read parity, *SVCE*, 438
 tag control store, *TECH*, 9–8
 tag store, *TECH*, 9–8
 TGEC heartbeat collision, *TECH*, 17–34
 UETP, *SVCE*, 357
 uncorrectable EDC, *TECH*, 9–15

Ethernet
 booting, *TECH*, 23–6
 interface selection, *TECH*, 17–1
 invoking console mode across, *OWNR*, 2–5
 loopback tests, *SVCE*, 271
 ports, testing, *SVCE*, 271
 preparing for UETP, *SVCE*, 337

Ethernet adapter, *TECH*, 17–1

Ethernet controllers, *TECH*, 1–24

Ethernet fuses
 removal and replacement, *SVCE*, 527

Ethernet ports, *TECH*, 1–48; *OWNR*, 2–2

Ethernet station address ROM, *TECH*,
 1-46, 18-48
 eval command, *TECH*, D-29
 Event logs, *SVCE*, 34
 examine command, *TECH*, D-31
 accessing pmem device (example), *TECH*,
 25-8
 referencing registers, *TECH*, 25-9
 used as abbreviation (example), *TECH*,
 25-8
 with address implied, *TECH*, 25-8
 with explicit address, *TECH*, 25-8
 Exception address register, *TECH*, 4-8
 Exception handling, *TECH*, 9-2
 Exceptions, *TECH*, 9-1
 causes, *TECH*, 9-1
 how PALcode handles, *SVCE*, 367
 machine checks, *TECH*, 9-2
 multiple, *TECH*, 9-1
 PALcode 0020 entry characteristics,
 TECH, 9-3
 PAL priority level, *TECH*, 9-3
 PAL routine behavior, *TECH*, 9-7
 parse tree PALcode entry 0020, *TECH*,
 9-3
 Exception summary register, *TECH*, 4-11
 EXC_ADDR, *TECH*, 4-8
 EXC_SUM, *TECH*, 4-11
 exer command, *TECH*, D-34
 exer_read command, *TECH*, D-40; *SVCE*,
 226
 exer_write command, *TECH*, D-41; *SVCE*,
 235
 exit command, *TECH*, D-42
 Expanders
 control power bus, *SVCE*, 609
 mass storage, *SVCE*, 608
 External devices, *OWNR*, 1-11
 connecting to the system, *OWNR*, 6-7
 guidelines for connecting, *OWNR*, 6-18

F

F0-F31, *TECH*, 3-12
 F31, *TECH*, 3-12
 Fan failure, *SVCE*, 68
 Fans
 removal and replacement, *SVCE*, 515,
 531
 Fan startup, *TECH*, 21-4
 Fast External Cache Write Hit, *TECH*, 7-3
 Fast SCSI
 described, *OWNR*, 5-5
 extending, *OWNR*, 6-18
 Fast SCSI 3.5-inch disk drive
 removal and replacement, *SVCE*, 489
 Fault detection/correction, *SVCE*, 368
 KFA40 I/O module, *SVCE*, 368
 KN430 processor module, *SVCE*, 368
 MS430 memory modules, *SVCE*, 368
 system bus, *SVCE*, 368
 Fault management, *TECH*, 10-1
 Faults, interpreting, *SVCE*, 411
 Fbus
 See Futurebus+
 fbus_diag command, *TECH*, D-43; *SVCE*,
 245
 fbus_sizer, *TECH*, D-45
 FEPR0M, *TECH*, 1-24, 18-48
 code structure, *TECH*, 1-45
 defined, *TECH*, 1-45
 FEPR0MS, *TECH*, 1-45
 FEPR0M unloading, *TECH*, 21-10
 FERR1, *TECH*, 13-22
 FERR2, *TECH*, 13-23
 FETCH, *TECH*, 5-22
 FETCH cycle, *TECH*, 7-1
 FETCHM, *TECH*, 5-22
 FETCHM cycle, *TECH*, 7-1
 FETCHM transaction, *TECH*, 7-7
 FETCH transaction, *TECH*, 7-7
 FEU, *TECH*, 1-41
 FHVECT, *TECH*, 13-22

FIFO queue, *TECH*, 14-1

Fill address register, *TECH*, 4-33

Fill syndrome register, *TECH*, 4-34

FILL_ADDR, *TECH*, 4-33

FILL_SYNDROME, *TECH*, 4-34

Filtering output
 using pipes and grep, *TECH*, 25-10

find_field command, *TECH*, D-46

Firmware
 console commands, *SVCE*, 41
 console emulation and diagnostics,
 TECH, 1-45
 defined, *TECH*, 1-43
 diagnostics, *SVCE*, 168
 overview, *TECH*, 1-43
 power-up diagnostics, *SVCE*, 136
 upgrade time, *TECH*, 1-45

FIVECT, *TECH*, 13-21

Fixed-disk drives, *OWNR*, 5-5
 See also Disk drives; specific drives

Fixed-media compartments, *SVCE*, 597

Fixed-media storage
 removal and replacement, *SVCE*, 488

Flags, *TECH*, 23-5
 BIP, *TECH*, 24-2
 bootstrap in progress, *TECH*, 23-2
 cold start, *TECH*, 23-2
 inverse filtering, *TECH*, 17-40

Flash-erase PROM, *TECH*, 18-48

Flash PROM
 See FEPRM

Floating-point registers, *TECH*, 3-12

Flow control
 syntax for constructs, *TECH*, 25-14

Flush instruction cache ASM register,
 TECH, 4-22

Flush instruction cache register, *TECH*,
 4-22

FLUSH_IC, *TECH*, 4-22

FLUSH_IC_ASM, *TECH*, 4-22

FMBPR, *TECH*, 13-19

free command, *TECH*, D-47

FRUs
 See also Removal and Replacement

FRUs (cont'd)
 commands to report errors, *SVCE*, 185,
 205
 for repair, *SVCE*, 544
 front, *SVCE*, 481
 rear, *SVCE*, 523
 removal and replacement, *SVCE*, 478,
 481, 523

Fuses, Ethernet, *SVCE*, 527

Futurebus+
 described, *OWNR*, 7-4, 7-11
 features of, *SVCE*, 587
 module location, *OWNR*, 1-7
 option LEDs, *SVCE*, 86
 routing, *TECH*, 1-13

Futurebus+ adapters, *TECH*, 15-1

Futurebus+ address space, *TECH*, 15-1,
 15-2

Futurebus+ interrupts, *TECH*, 14-1

Futurebus+ mailbox command field, *TECH*,
 13-31

Futurebus+ mailbox status field, *TECH*,
 13-33

Futurebus+ module
 removal and replacement, *SVCE*, 525

Futurebus+ slots, *TECH*, 1-36

F_floating, *TECH*, 3-3

F_floating load exponent mapping, *TECH*,
 3-3

G

grep command, *TECH*, 25-10, D-48
 See also pipe(|) command

Grounding wrist strap, *OWNR*, 8-6

G_floating, *TECH*, 3-4

H

H7178, *TECH*, 1-42

H7179, *TECH*, 1-42

H7851, *TECH*, 1-41

H7853, *TECH*, 1-41

Halt button
 location, *OWNR*, 1-6
 using, *OWNR*, 1-18
 Halt procedure, *OWNR*, 1-18
 Halt startup action, *OWNR*, 4-5
 Halt switch, *TECH*, 1-9
 and system interrupts, *TECH*, 14-3
 Hang, system, *SVCE*, 359
 Hard errors
 defined, *TECH*, 1-31
 Hardware, installing
 See the *DEC 4000 Quick Installation* card
 Hardware error interrupts, *TECH*, 14-2
 Hardware interrupt enable register, *TECH*, 4-16
 Hardware interrupt request register, *TECH*, 4-13
 Hardware invalidates, *TECH*, 5-22
 Hardware restart parameter block, *TECH*, 23-3
 hd command, *TECH*, D-50
 Head cleaning, *OWNR*, 5-40
 Head cleaning cassette, *OWNR*, 5-40
 Heartbeat collision check, *TECH*, 17-34
 Help
 accessing all types, *OWNR*, 1-22
 accessing in console mode, *OWNR*, 3-3
 types available, *OWNR*, 1-22
 help command, *TECH*, D-51; *OWNR*, 3-13
 hex dump (example), *TECH*, 25-9
 hex dump command
 dumping memory, *TECH*, 25-9
 Hexword read transactions
 non-cacheable, *TECH*, 1-29
 Hexword write transactions
 non-cacheable, *TECH*, 1-29
 HIER, *TECH*, 4-16
 HIRR, *TECH*, 4-13
 HISTRY local program, *SVCE*, 293
 HWRPB, *TECH*, 23-3
 HWRPBSQ_RESTART, *TECH*, 24-2

I
 I/O
 for removable media, *TECH*, 1-2
 I/O bus, Futurebus+ features, *SVCE*, 587
 I/O expansion slots, *TECH*, 1-36
 I/O module, *SVCE*, 577
 described, *OWNR*, 7-7
 diagnostic address register map, *TECH*, 13-5
 functional diagram, *TECH*, 1-22
 Futurebus+ diagnostic register map, *TECH*, 13-3
 hardware error interrupt conditions, *TECH*, 14-2
 lbus diagnostic register map, *TECH*, 13-3
 location, *OWNR*, 1-7
 register map, *TECH*, 13-2
 removal and replacement, *SVCE*, 525
 I/O panel LEDs, *SVCE*, 82
 I/O redirection
 to other devices, *TECH*, 25-11
 I/O subsystem, *OWNR*, 7-4
 I-box internal processor registers, *TECH*, 4-2
 ICCSR, *TECH*, 4-4
 ID, *TECH*, 18-8
 for environment variables, *TECH*, 23-2
 Idle bus, *TECH*, 19-13
 Idle cycles, *TECH*, 1-30
 Imperfect filtering, *TECH*, 17-42
 init command, *OWNR*, 3-14
 init -driver command, *SVCE*, 120
 Initialization, *TECH*, 21-6; *SVCE*, 361
 and reset, *TECH*, 11-3
 and the backup cache, *TECH*, 11-1
 and the CPU clocks, *TECH*, 11-3
 of the duplicate tag store, *TECH*, 11-3
 of the system bus interface, *TECH*, 11-3
 Initialization flow diagram, *TECH*, 21-7, 21-9, 21-11

initialization signal, *TECH*, 19-17
 initialize, *TECH*, D-53
 Insert mode, *OWNR*, 2-8
 Installation procedure
 See the *DEC 4000 Quick Installation* card
 Installation recommendations, *SVCE*, 31
 Instruction cache control and status register,
 TECH, 4-4
 Instruction formats, *TECH*, 3-12
 Instruction translation buffer ASM, *TECH*,
 4-10
 Instruction translation buffer IS register,
 TECH, 4-10
 Instruction translation buffer page table
 entry register, *TECH*, 4-3
 Instruction translation buffer page table
 entry temporary register, *TECH*, 4-7
 Instruction translation buffer zap register,
 TECH, 4-10
 Interleave, *TECH*, 1-30
 Internal processor register format, *TECH*,
 4-8
 Internal processor registers
 and initialization, *TECH*, 11-1
 Interprocessor interrupt request register,
 TECH, 6-14
 Interrupt encoding, *TECH*, 14-1
 Interrupt handling, *TECH*, 9-10
 Interrupts, *TECH*, 1-31, 9-1, 14-1
 and the interrupt vector register, *TECH*,
 14-2
 CIRQ_L[0], *TECH*, 14-2
 entry into PALcode, *TECH*, 9-10
 Futurebus+, *TECH*, 14-1
 hardware error, *TECH*, 14-2
 local I/O, *TECH*, 14-2
 non-processor generated, *TECH*, 9-9
 processor generated, *TECH*, 9-1
 TGEC, *TECH*, 17-45
 Interrupts and exceptions
 backup cache tag parity error, *TECH*,
 9-7
 Invalidates
 system bus caused, *TECH*, 8-1

Inverse_filtering flag, *TECH*, 17-40
 IOCSR, *TECH*, 13-6
 IOG L, *TECH*, 19-10
 IOREQ L, *TECH*, 19-10
 io_diag, *TECH*, D-54
 ISTAT, *TECH*, 18-34, 18-35
 ITBASM, *TECH*, 4-10
 ITBIS, *TECH*, 4-10
 ITBZAP, *TECH*, 4-10
 ITB_PTE, *TECH*, 4-3
 ITB_PTE_TEMP, *TECH*, 4-7

K

Keyboard, maintenance, *OWNR*, 8-10
 Keyboard characters, supported in console
 mode, *OWNR*, 2-6, 2-8
 Keys
 See Keyboard characters; System keys
 KFA40 I/O module, *TECH*, 1-22; *SVCE*,
 577
 kill command, *TECH*, D-55; *SVCE*, 274
 kill_diags command, *TECH*, D-56; *SVCE*,
 274
 KN430 CPU, *SVCE*, 562
 KN430 CPU subsystem, *TECH*, 1-14
 KN430 processor, *TECH*, 2-2

L

Labeling
 mass storage media, *OWNR*, 5-38
 system name, *OWNR*, 8-3
 Labels, language, replacing, *OWNR*, 8-4
 language environment variable
 changing default, *OWNR*, 4-14
 described, *OWNR*, 4-2
 displaying default, *OWNR*, 4-14
 Language labels, replacing, *OWNR*, 8-4
 Language setting
 changing default, *OWNR*, 4-14
 displaying current default, *OWNR*, 4-14
 Lbus addressing, *TECH*, 16-1

Lbus mailbox command field, *TECH*, 13–35
 Lbus mailbox status field, *TECH*, 13–36
 LCRC, *TECH*, 18–38
 LDxL cycle, *TECH*, 7–2
 LDxL transaction, *TECH*, 7–6
 LEDs
 functions of, *SVCE*, 65
 Futurebus+ options, *SVCE*, 86
 I/O panel, *SVCE*, 82
 interpreting, *SVCE*, 62, 64
 on options during power-up, *SVCE*, 43
 operator control panel, *SVCE*, 76
 power supply, *SVCE*, 67
 storage device, *SVCE*, 90
 LERR1, *TECH*, 13–26
 LERR2, *TECH*, 13–27
 line command, *TECH*, D–57
 Line printer, preparing for UETP, *SVCE*, 310, 334
 LINT, *TECH*, 13–24
 Listing contents of a script
 using cat command, *TECH*, 25–12
 LMBPR, *TECH*, 13–18
 Local I/O bus
 routing, *TECH*, 1–13
 Local I/O devices, *TECH*, 16–1
 Local I/O interrupts, *TECH*, 14–2
 Local programs
 See Programs, local
 Lock registers, *TECH*, 3–12
 Log files
 See also UETP.LOG file
 accounting, *SVCE*, 49
 console event, *SVCE*, 49
 generated by UETP, *SVCE*, 352
 OLDUETP.LOG, *SVCE*, 354
 operator, *SVCE*, 49
 sethost, *SVCE*, 49
 Logs
 event, *SVCE*, 34
 maintenance, *SVCE*, 61
 Longword, *TECH*, 3–2

Longword integer format in FPU, *TECH*, 3–9
 Loopback
 and the TGEC, *TECH*, 17–50
 Loopback tests, *SVCE*, 39, 266
 auxiliary serial port, *SVCE*, 267
 command summary, *SVCE*, 283
 Ethernet, *SVCE*, 271
 ls command, *TECH*, D–58

M

Machine check/interrupts
 processor, *SVCE*, 370
 processor corrected, *SVCE*, 370
 system, *SVCE*, 370
 Machine checks, *TECH*, 9–2
 Magnetic tape
 preparing for UETP, *SVCE*, 310, 324
 Mailbox, *TECH*, 13–28
 defined, *TECH*, 1–33
 format, *TECH*, 13–29
 mapping, *TECH*, 16–2
 Mailbox pointer register, *TECH*, 13–29
 Maintenance, *OWNR*, 8–9
 of mass storage media and devices, *OWNR*, 5–37
 of monitor keyboards, *OWNR*, 8–10
 of system unit, *OWNR*, 8–10
 Maintenance log, *SVCE*, 61
 Maintenance strategy, *SVCE*, 9, 33
 field feedback, *SVCE*, 60
 information services, *SVCE*, 51
 service delivery, *SVCE*, 27
 service tools and utilities, *SVCE*, 33
 Mass storage
 See also Mass storage devices; Mass storage media
 actions before operating devices, *OWNR*, 5–2
 compartments, location, *OWNR*, 5–2
 configuration rules, *SVCE*, 602
 described, *SVCE*, 596
 devices supported in the DEC 4000 AXP, *OWNR*, 5–4

Mass storage (cont'd)

- finding additional information on, *OWNR*, 5-42
 - fixed-media, described, *SVCE*, 597
 - front panel, *TECH*, 1-36
 - media, labeling, *OWNR*, 5-38
 - removable-media, described, *SVCE*, 603
- Mass storage adapters, *OWNR*, 7-10
- Mass storage area, *TECH*, 1-34
- Mass storage compartments
- bus names, *OWNR*, 6-8
 - location, *OWNR*, 1-5, 5-2
- Mass storage devices
- See also Drive ID plugs
- actions before operating, *OWNR*, 5-2
 - changing drive ID plugs, *OWNR*, 6-23
 - changing DSSI device parameters, *OWNR*, 6-24
 - cluster capability, *OWNR*, 6-4
 - connecting external, *OWNR*, 6-18
 - drive ID plugs, *OWNR*, 6-8
 - finding additional information on, *OWNR*, 5-42
 - function of, *OWNR*, 7-10
 - labeling, *OWNR*, 5-38
 - list of, *OWNR*, 5-4
 - maintaining, *OWNR*, 5-37
 - mounting, *OWNR*, 5-2
 - supported in the DEC 4000 AXP, *OWNR*, 5-4
- Mass storage media
- labeling, *OWNR*, 5-38
 - maintaining, *OWNR*, 5-37
 - write-protecting and write-enabling, *OWNR*, 5-37

Media

- See Mass storage media
- memexer command, *TECH*, D-59; *SVCE*, 214
- memexer_mp command, *TECH*, D-60; *SVCE*, 220

Memory

- bad on power-up, *TECH*, 11-3
- configuring, *TECH*, 26-9
- displaying, *OWNR*, 6-12

Memory, main

- exercising, *SVCE*, 214
- Memory exchange transactions, *TECH*, 19-26
- Memory-like locations
- defined, *TECH*, 7-7
- Memory management control and status register, *TECH*, 4-21
- Memory module
- displaying information for, *SVCE*, 630
 - MS430, *SVCE*, 575
 - removal and replacement, *SVCE*, 525
- Memory modules, *OWNR*, 7-7
- MS430, *SVCE*, 569
- Memory move
- and SFBR, *TECH*, 18-15
- Memory prefetch register, *TECH*, 3-12
- Memory slot ID code, *TECH*, 19-19
- Memory testing, *TECH*, 21-13
- Memory write transactions, *TECH*, 19-28
- memtest command, *TECH*, D-61
- Microcontroller
- startup firmware, *TECH*, 1-45
- Microprocessor chip
- See DECchip 21064 microprocessor
- MID<1:0>, *TECH*, 19-19
- Miss address register, *TECH*, 6-17
- MM_CSR, *TECH*, 4-21
- Module order, *TECH*, 1-17
- Modules
- CPU features, *SVCE*, 564
 - front end unit, *TECH*, 1-41
 - KFA40, *TECH*, 1-22
 - KFA40 I/O, *SVCE*, 577
 - KN430 CPU, *SVCE*, 562
 - KN430 processor, *TECH*, 1-17, 1-19
 - memory, *TECH*, 1-26
 - MS430 variations, *SVCE*, 569
 - power system controller, *TECH*, 1-41
 - storage backplane, *TECH*, 1-11
 - system, *OWNR*, 6-6
 - system backplane, *TECH*, 1-13
 - 3 volt converter, *TECH*, 1-42
 - 5 volt converter, *TECH*, 1-42

Monarch processor, *TECH*, 15-1
Monitoring status
 using ps command (example), *TECH*,
 25-12
 using show-status command (example),
 TECH, 25-12
MOP
 must transact operaton, *TECH*, 23-7
Mop booting, *TECH*, 23-7
more command, *OWNR*, 3-4
MS430 memory modules, *SVCE*, 569
Multiple exceptions, *TECH*, 9-1
Multiprocessor bootstrap, *SVCE*, 162
Multiprocessor configuration CSR definitions,
 TECH, 6-13

N

net command, *TECH*, D-64
nettest command, *TECH*, D-67
Network, testing, *SVCE*, 271
Networked system, *OWNR*, 6-2
Network listening, *TECH*, 23-7
Node name, labeling, *OWNR*, 8-3
NODENAME parameter, *OWNR*, 6-27;
 SVCE, 672
Noncacheable address sapce write
 transaction, *TECH*, 19-30
Non-memory like locations
 defined, *TECH*, 7-7
Non-stalled transaction times, *TECH*, 19-2
Nonvolatile EEPROM, *TECH*, 6-23
NT AXP operating system, *OWNR*, 7-3
Null, *TECH*, 19-24
Numbering Conventions, *TECH*, xxxii
NUT, *TECH*, 19-24
nvram file, *SVCE*, 120

O

OCP
 See Operator control panel
 See Operator control panel

OCP halt request buffer, *TECH*, 6-23
OLDUETP.LOG file, *SVCE*, 352
On-line help
 available topics, *TECH*, 25-6
 brief, *TECH*, 25-5
 | more, *TECH*, 25-7
 multiple topics, *TECH*, 25-6
 screen display, *TECH*, 25-5
 wildcarding (example), *TECH*, 25-7
Online help
 in console mode, *OWNR*, 3-3
Open VMS AXP
 event record translation, *SVCE*, 398
OpenVMS AXP operating system
 booting software on, *OWNR*, 1-16
 compatibility with DEC 4000 AXP,
 OWNR, 7-3
 shutdown, *OWNR*, 1-17
Operating system
 boot failures, reporting, *SVCE*, 19, 26
 crash dumps, *SVCE*, 47
 exercisers, *SVCE*, 45
Operating system mode
 defined, *OWNR*, 1-10
 returning to from console mode, *OWNR*,
 1-19
Operating system restart, *TECH*, 24-2
Operating systems, supported on DEC 4000
 AXP, *OWNR*, 7-3
Operating system software, booting, *OWNR*,
 1-15
Operator control panel, *TECH*, 1-6
 controls, *OWNR*, 1-6
 location, *OWNR*, 1-5
 operations, *OWNR*, 1-17
 removal and replacement, *SVCE*, 483
 shutting down system before using,
 OWNR, 1-17
 using self-test lights on, *OWNR*, 1-21
Operator control panel LEDs, *SVCE*, 76
Options, *OWNR*, 6-6
 See the *DEC 4000 Options Guide*
OSF
 See DEC OSF/1 AXP operating system

Overstrike mode, *OWNR*, 2–8
Overtemperature, *SVCE*, 68
Ownership flag, *TECH*, 1–31

P

PALcode

See show pal command

PALcode entry characteristics, *TECH*, 9–10

PAL priority level, *TECH*, 9–10

PAL_BASE, *TECH*, 4–13

PAL_TEMP, *TECH*, 4–28

Parameters, DSSI, *OWNR*, 6–24

PARAMS local program, *SVCE*, 293

Parse trees

PALcode entry, *TECH*, 9–11

PC, *TECH*, 3–11

PCD8584, *TECH*, 18–48

PECL, *TECH*, 1–21

Perfect filtering, *TECH*, 17–40

PHI1 and PHI1 L, *TECH*, 19–18

PHI3 and PHI3 L, *TECH*, 19–18

Physical address space, *TECH*, 1–32, 1–33

Physical cache, *TECH*, 8–1

Pipe (|) command, *TECH*, 25–10

See also grep command

pmem:

physical memory, *TECH*, 25–8

Ports

AC power, *TECH*, 1–48

Ethernet, *TECH*, 1–48

SCSI storage expansion, *TECH*, 1–48

serial line, *TECH*, 1–47

Power

diagnostic flow, *SVCE*, 21

troubleshooting, *SVCE*, 18

Power control bus, *SVCE*, 609

Power-down mode, *TECH*, 18–25

Power-down procedure, *OWNR*, 1–21

Power-on tests, *SVCE*, 122

Power problems

diagnostic flow, *SVCE*, 21

PSC failure, *SVCE*, 67

troubleshooting, *SVCE*, 18

Power subsystem, *OWNR*, 7–4

components, *OWNR*, 7–8

location, *OWNR*, 1–7

Power subsystem components, *SVCE*, 590

Power supply

and system event, *TECH*, 14–3

indicators, *TECH*, 1–38

LEDs, *SVCE*, 67

removal and replacement, *SVCE*, 529

Power-up, *SVCE*, 122

option LEDs, *SVCE*, 43

with bad main memory, *TECH*, 11–3

Power-up baud rate switch, *TECH*, 1–9

Power-up procedure, *OWNR*, 1–12

actions before beginning, *OWNR*, 1–11

task overview, *OWNR*, 1–11

Power-up screens, *OWNR*, 1–13; *SVCE*, 95

Power-up sequence, *TECH*, 11–3; *SVCE*,
122

AC, *SVCE*, 127

DC, *SVCE*, 131

mass storage failures, *SVCE*, 104

robust mode, *SVCE*, 116

Primary processor functions, *TECH*, 1–18

Privileged architecture library base register,
TECH, 4–13

Processor caused invalidates, *TECH*, 8–1

Processor initiated transactions, *TECH*, 7–2

Processor mailbox register, *TECH*, 6–13

Processor module

configurations, *TECH*, 1–14

differences, *TECH*, 1–14

Processor registers

symbolic reference, *TECH*, 25–10

Processor status register, *TECH*, 4–11

Process registers

pc, sp, ps (example), *TECH*, 25–10

Product delivery plan, *SVCE*, 56

Program mode

See Operating system mode, *OWNR*,
1–10

Programs, local

DIRECT, *SVCE*, 293

DKUTIL, *SVCE*, 293

DRVEXR, *SVCE*, 293

Programs, local (cont'd)

DRVTST, *SVCE*, 293
ERASE, *SVCE*, 293
HISTRY, *SVCE*, 293
PARAMS, *SVCE*, 293
VERIFY, *SVCE*, 293

Protocol signals, *TECH*, 19–10

PS, *TECH*, 3–11, 4–11

PSC, *TECH*, 1–41

startup firmware, *TECH*, 1–44

psc command, *TECH*, D–71

ps command, *TECH*, D–70

Q

Quadword, *TECH*, 3–2

Quadword integer format in FPU, *TECH*,
3–9

R

R30, *TECH*, 3–11

R31, *TECH*, 3–11

R400X expander, *OWNR*, 7–10

RAM

for SCSI controllers, *TECH*, 1–46

RDES0 word, *TECH*, 17–29

RDES1 word, *TECH*, 17–31

RDES2 word, *TECH*, 17–32

RDES3 word, *TECH*, 17–32

Read

to secondary bus, *TECH*, 13–36

Read and write transactions, *TECH*, 19–20

READ_BLOCK, *TECH*, 7–1

READ_BLOCK, *TECH*, 7–4

Reboot

limitations on a secondary processor,
TECH, 24–2

Reboot procedure, *OWNR*, 1–15

Receive descriptors, *TECH*, 17–28

Receive descriptor status validity, *TECH*,
17–33

Redirecting output, *TECH*, 25–11

using append operator (>), *TECH*,
25–14

Redirecting output (cont'd)

using redirection operator (>), *TECH*,
25–11

Redirecting output (example), *TECH*, 25–11

Reduced instruction set computer

See RISC technology

Registers

A-box control, *TECH*, 4–23

adder sum output, *TECH*, 18–47

Alpha IPRs, *TECH*, 3–12

Alpha optional, *TECH*, 3–12

alternate processor mode, *TECH*, 4–24

asynchronous system trap enable, *TECH*,
4–17

asynchronous trap request, *TECH*, 4–15

AUX_CTRL, *TECH*, 16–4

AUX_Data, *TECH*, 16–4

backup cache control, *TECH*, 5–3

backup cache correctable error, *TECH*,
5–8

backup cache correctable error address,
TECH, 5–11

backup cache tag, *TECH*, 4–36

backup cache uncorrectable error, *TECH*,
5–12

backup cache uncorrectable error address,
TECH, 5–15

bus interface control unit, *TECH*, 4–26

bus interface unit address, *TECH*, 4–32

bus interface unit status, *TECH*, 4–31

C³ revision, *TECH*, 6–18

chip test eight, *TECH*, 18–37

chip test five, *TECH*, 18–29

chip test four, *TECH*, 18–28

chip test one, *TECH*, 18–25

chip test seven, *TECH*, 18–32

chip test six, *TECH*, 18–31

chip test three, *TECH*, 18–27

chip test two, *TECH*, 18–26

chip test zero, *TECH*, 18–24

console control, *TECH*, 16–5

console data, *TECH*, 16–5

cycle counter, *TECH*, 4–25

cycle counter control, *TECH*, 4–25

data cache status, *TECH*, 4–29

Registers (cont'd)

- data structure address, *TECH*, 18–23
- data translation buffer ASM, *TECH*, 4–22
- data translation buffer invalidate signal, *TECH*, 4–22
- data translation buffer page table entry, *TECH*, 4–19
- data translation buffer page table entry temporary, *TECH*, 4–20
- data translation buffer zap, *TECH*, 4–22
- descriptor list addresses register, *TECH*, 17–9
- diagnostic control and status, *TECH*, 13–20
- DMA byte counter, *TECH*, 18–39
- DMA command, *TECH*, 18–39
- DMA control, *TECH*, 18–45
- DMA FIFO, *TECH*, 18–33
- DMA interrupt enable, *TECH*, 18–43
- DMA mode, *TECH*, 18–42
- DMA next data address, *TECH*, 18–40
- DMA scripts pointer save, *TECH*, 18–41
- DMA status, *TECH*, 18–17
- DMA watchdog timer, *TECH*, 18–45
- DMS scripts pointer, *TECH*, 18–40
- duplicate tag error, *TECH*, 5–20
- exception address, *TECH*, 4–8
- exception summary, *TECH*, 4–11
- explicit reference, *TECH*, 25–9
- fill address, *TECH*, 4–33
- fill syndrome, *TECH*, 4–34
- floating-point, *TECH*, 3–12
- flush instruction cache, *TECH*, 4–22
- flush instruction cache ASM, *TECH*, 4–22
- Futurebus+ error 1, *TECH*, 13–22
- Futurebus+ error 2, *TECH*, 13–23
- Futurebus+ halt vector, *TECH*, 13–22, 14–4
- Futurebus+ interrupt vector, *TECH*, 13–21
- Futurebus+ mailbox pointer, *TECH*, 13–19
- GTEC command and mode, *TECH*, 17–17

Registers (cont'd)

- hardware interrupt enable, *TECH*, 4–16
- hardware interrupt request, *TECH*, 4–13
- I/O control and status, *TECH*, 13–6, 14–4
- I/O diagnostic mode address, *TECH*, 13–5
- implicit reference, *TECH*, 25–9
- instruction cache control and status, *TECH*, 4–4
- instruction translation buffer ASM, *TECH*, 4–10
- instruction translation buffer page table entry, *TECH*, 4–3
- instruction translation buffer page table entry temporary, *TECH*, 4–7
- instruction translation buffer zap, *TECH*, 4–10
- integer, *TECH*, 3–11
- interprocessor interrupt, *TECH*, 1–31
- interprocessor interrupt request, *TECH*, 6–14
- interprocessor mailbox, *TECH*, 1–31
- interrupt status, *TECH*, 18–34, 18–35
- intr-flag, *TECH*, 3–12
- intruction translation buffer IS, *TECH*, 4–10
- Lbus error 1, *TECH*, 13–26
- lbus error 2, *TECH*, 13–27
- Lbus mailbox pointer, *TECH*, 13–18
- local interrupt, *TECH*, 13–24, 14–2
- lock, *TECH*, 3–12
- longitudinal parity, *TECH*, 18–38
- mailbox pointer, *TECH*, 13–29
- memory management control and status, *TECH*, 4–21
- memory prefetch, *TECH*, 3–12
- miss address, *TECH*, 6–17
- multiprocessor configuration CSR, *TECH*, 6–13
- noncacheable address space silo, *TECH*, 1–31
- privileged architecture library base, *TECH*, 4–13
- processor mailbox, *TECH*, 6–13
- processor status, *TECH*, 3–11, 4–11
- program counter, *TECH*, 3–11

Registers (cont'd)

- readable noncacheable address space
 - device request, *TECH*, 1-31
- receive polling register, *TECH*, 17-8
- scratch register, *TECH*, 18-41
- SCSI bus control lines, *TECH*, 18-16
- SCSI bus data lines, *TECH*, 18-16
- SCSI chip ID, *TECH*, 18-9
- SCSI control, *TECH*, 18-4
- SCSI control 1, *TECH*, 18-7
- SCSI Destination ID 02 (01), *TECH*, 18-8
- SCSI first byte received, *TECH*, 18-15
- SCSI input data latch, *TECH*, 18-15
- SCSI interrupt enable, *TECH*, 18-9
- SCSI output control latch, *TECH*, 18-13
- SCSI output data latch, *TECH*, 18-13
- SCSI status 0, *TECH*, 18-19
- SCSI status 1, *TECH*, 18-21
- SCSI status 2, *TECH*, 18-22
- SCSI transfer, *TECH*, 18-10
- serial line clear, *TECH*, 4-9
- serial line receive, *TECH*, 4-10
- serial line transmit, *TECH*, 4-18
- silos, *TECH*, 1-31
- software interrupt enable, *TECH*, 4-17
- software interrupt request, *TECH*, 4-15
- symbolic reference, *TECH*, 25-9
- system bus, *TECH*, 6-1
- system bus control, *TECH*, 6-1
- system bus error, *TECH*, 6-4
- system bus error 1, *TECH*, 13-11
- system bus error 2, *TECH*, 13-17
- system bus error 3, *TECH*, 13-18
- system bus error address low, *TECH*, 6-10
- system interrupt clear, *TECH*, 6-14
- temporary stack, *TECH*, 18-33
- TGEC boot message, *TECH*, 17-26
- TGEC command and status, *TECH*, 17-3
- TGEC diagnostic, *TECH*, 17-28
- TGEC identification and missed frame count, *TECH*, 17-25
- TGEC reserved, *TECH*, 17-23
- TGEC status, *TECH*, 17-12

Registers (cont'd)

- TGEC system base, *TECH*, 17-22
- TGEC vector address, *TECH*, 17-5
- TGEC watchdog timer, *TECH*, 17-23
- TOY, *TECH*, 1-25, 1-46
- TOY clock, *TECH*, 16-6
- translation buffer control, *TECH*, 4-19
- Transmit polling demand, *TECH*, 17-7
- VAX compatibility registers, *TECH*, 3-12
- virtual address, *TECH*, 4-22

Registers

- system bus error address high, *TECH*, 6-11
- TOY A (TOYA), *TECH*, 16-7
- TOY B (TOYB), *TECH*, 16-9
- TOY C (TOYC), *TECH*, 16-11
- TOY D (TOYD), *TECH*, 16-12

Relative addresses

- symbolic reference (example), *TECH*, 25-9

Remote access devices

- defined, *OWNR*, 2-2
- using, *OWNR*, 2-5
- using to log in to the console, *OWNR*, 2-5

Remote boot

- and system event, *TECH*, 14-3

Remote console device

- changing baud rate of, *OWNR*, 4-15
- using, *OWNR*, 2-5

Removable media, labeling, *OWNR*, 5-38

Removable-media compartments

- configuration rules, *SVCE*, 606
- described, *SVCE*, 603

Removable-media drives

- See Tape drives; specific drives

Removable-media storage, *TECH*, 1-2

- removal and replacement, *SVCE*, 508

Removable-media storage I/O, *TECH*, 1-2

Removal and replacement

- backplane, *SVCE*, 535
- CPU module, *SVCE*, 525
- Futurebus+ module, *SVCE*, 525
- guidelines, *SVCE*, 478
- I/O module, *SVCE*, 525
- memory module, *SVCE*, 525

Removal and replacement (cont'd)

- power supply, *SVCE*, 529
- rear FRUs, *SVCE*, 523
- returning FRUs, *SVCE*, 544

REQ_PROGRAM, *TECH*, 23–7

Reset, *TECH*, 21–5

- and the OCP, *TECH*, 21–5
- of the TGEC, *TECH*, 17–44

Reset button

- location, *OWNR*, 1–6
- using, *OWNR*, 1–20

Reset procedure, *OWNR*, 1–20

Reset switch, *TECH*, 1–8

Responder, *TECH*, 19–19

Response and interrupt signals, *TECH*, 19–14

Restart, *TECH*, 24–2

- startup action, *OWNR*, 4–5

Restart and boot code, *TECH*, 1–46

Restart failure, *TECH*, 24–2

Restart parameters, *TECH*, 24–3

RF36 drive

- components, *OWNR*, 5–6
- described, *OWNR*, 5–5
- hardware specifications, *OWNR*, 5–4
- lights, *OWNR*, 5–7
- write-protecting and write-enabling, *OWNR*, 5–8

RF73 drive

- components, *OWNR*, 5–6
- described, *OWNR*, 5–5
- hardware specifications, *OWNR*, 5–4
- lights, *OWNR*, 5–7
- write-protecting and write-enabling, *OWNR*, 5–8

RF-series drive local programs, *SVCE*, 292

RF-series drives

- capacity allowed in R400X, *OWNR*, 7–10
- changing device parameters for, *OWNR*, 6–24
- changing drive ID plugs, *OWNR*, 6–23
- cluster capability, *OWNR*, 6–4
- described, *OWNR*, 5–5
- lights, *OWNR*, 5–7

RF-series drives (cont'd)

- write-protecting and write-enabling, *OWNR*, 5–8

RF-series ISE

- diagnostics, *SVCE*, 284
- errors, *SVCE*, 288

RISC technology, *OWNR*, 7–2

rm command, *TECH*, D–72

Robust mode, power-up, *SVCE*, 116

ROM

- Ethernet station address, *TECH*, 1–46, 18–48

ROM-based diagnostics (RBDs)

- advantages, *SVCE*, 36
- commands to report errors, *SVCE*, 173
- diagnostic-related commands, *SVCE*, 176
- performing extended testing and exercising, *SVCE*, 174
- running, *SVCE*, 168
- utilities, *SVCE*, 171

Root number, *OWNR*, 4–10

Round-robin, *TECH*, 1–30

RRD42 compact disc drives

- See RRD42 drives

RRD42 compact discs

- caring for, *OWNR*, 5–38
- handling, *OWNR*, 5–38

RRD42 drives

- busy light, *OWNR*, 5–14
- components, *OWNR*, 5–12
- described, *OWNR*, 5–12
- hardware specifications, *OWNR*, 5–4
- inserting a disc into, *OWNR*, 5–14
- operating, *OWNR*, 5–12
- removing a disc from, *OWNR*, 5–14

RS-232, *TECH*, 16–2

Running tasks

- in background mode "&", *TECH*, 25–11
- in background mode "&" (example), *TECH*, 25–11

RZ26 drive

- components, *OWNR*, 5–6
- described, *OWNR*, 5–5
- hardware specifications, *OWNR*, 5–4
- lights, *OWNR*, 5–7

RZ26 drive (cont'd)
 write-protecting and write-enabling,
OWNR, 5–8

RZ36 drive
 components, *OWNR*, 5–6
 described, *OWNR*, 5–5
 hardware specifications, *OWNR*, 5–4
 lights, *OWNR*, 5–7
 write-protecting and write-enabling,
OWNR, 5–8

RZ73 drive
 components, *OWNR*, 5–6
 described, *OWNR*, 5–5
 hardware specifications, *OWNR*, 5–4
 lights, *OWNR*, 5–7
 write-protecting and write-enabling,
OWNR, 5–8

RZ-series drives
 capacity in R400X, *OWNR*, 7–10
 changing drive ID plugs, *OWNR*, 6–23
 described, *OWNR*, 5–5
 lights, *OWNR*, 5–7
 write-protecting and write-enabling,
OWNR, 5–8

S

sa command, *TECH*, D–73

SBCL, *TECH*, 18–16

SBDL, *TECH*, 18–16

SCID, *TECH*, 18–9

SCL signal, *TECH*, 19–19

SCNTL0, *TECH*, 18–4

SCNTL1, *TECH*, 18–7

SCRATCH, *TECH*, 18–41

Screen output, displaying, *OWNR*, 3–4

Script RAM Buffer, *TECH*, 18–47

Scrolling, preventing, *OWNR*, 3–4

SCSI, fast
 See Fast SCSI 3.5-inch disk drive
 described, *OWNR*, 5–5
 extending, *OWNR*, 6–18

SCSI 3.5-inch disk drive
 removal and replacement, *SVCE*, 493

SCSI 5.25-inch disk drive
 removal and replacement, *SVCE*, 497

SCSI bulkhead connector
 removal and replacement, *SVCE*, 509

SCSI buses, terminating and extending,
OWNR, 6–20

SCSI continuity card
 removal and replacement, *SVCE*, 511

SCSI controller
 revision level, *TECH*, 18–37

SCSI controller address decoding, *TECH*,
 16–1

SCSI controllers static RAM, *TECH*, 1–46

SCSI driver
 sizing, *TECH*, 26–23
 startup, *TECH*, 26–23

SCSI/DSSI Adapters, *TECH*, 18–1

SCSI/DSSI initialization, *TECH*, 21–15

SCSI ID plugs, *OWNR*, 6–8
 See also Drive ID plugs

SCSI storage expansion ports, *TECH*, 1–48

SCSI storageless tray assembly
 removal and replacement, *SVCE*, 499

SDA signal, *TECH*, 19–19

SDID, *TECH*, 18–8

Secondary buses, *TECH*, 1–33

Secondary bus read, *TECH*, 13–36

Secondary bus write, *TECH*, 13–37

Secondary I/O space, *TECH*, 13–28

Self-test
 checking results of, *OWNR*, 1–21
 screen display, *OWNR*, 1–13

Self-test status lights
 location, *OWNR*, 1–6
 using, *OWNR*, 1–21

semaphore command, *TECH*, D–74

Serial bus bus
 interface register map, *TECH*, 18–48

Serial control bus, *SVCE*, 581
 EEPROM, *TECH*, 1–47
 interface, *TECH*, 1–21, 18–48
 node addresses, *TECH*, 1–43
 routing, *TECH*, 1–13

Serial control bus signals, *TECH*, 19–19

Serial line
 units, *TECH*, 1–25

Serial line clear register, *TECH*, 4–9

Serial line receive register, *TECH*, 4–10

Serial lines
 differences, *TECH*, 1–47
 features, *TECH*, 1–47
 ports, *TECH*, 1–47

Serial line transmit register, *TECH*, 4–18

Serial line unit register map, *TECH*, 16–2

Serial line units, *TECH*, 16–2

Serial port, changing baud rate setting of,
 OWNR, 4–15

Service
 blitzes, *SVCE*, 57
 call-handling and management planning
 (CHAMP), *SVCE*, 61
 Digital services product delivery plan,
 SVCE, 56
 documentation set, *SVCE*, 53
 field feedback, *SVCE*, 60
 labor activity reporting system (LARS),
 SVCE, 61
 maintenance strategy overview, *SVCE*, 9
 methodology, *SVCE*, 27
 storage and retrieval system (STARS),
 SVCE, 58
 tools and utilities, *SVCE*, 33
 training, *SVCE*, 54

Service call, completing, *SVCE*, 60

set command, *TECH*, D–75, D–77; *OWNR*,
 3–16

set host command, *OWNR*, 3–19

set screen_mode command, *SVCE*, 101

SFBR, *TECH*, 18–15

sh, *TECH*, D–79

Shipping carton contents, *OWNR*, 8–2

show boot command
 See show bootdef_dev command

show command, *TECH*, D–80, D–83, D–84,
 D–85, D–87, D–89, D–90, D–91, D–92;
 OWNR, 3–21

show command (cont'd)
 See also show configuration command;
 show device command; show memory
 command; show pal command; show
 version command
 to display environment variables' status,
 OWNR, 4–2

show configuration command, *OWNR*, 6–10;
 SVCE, 614

show device command, *OWNR*, 6–13;
 SVCE, 619

show device du pu command, *OWNR*, 6–25;
 SVCE, 648

show error command, *SVCE*, 205

show fru command, *SVCE*, 185

show memory command, *OWNR*, 6–12;
 SVCE, 630

show pal command, *OWNR*, 6–15

show version command, *OWNR*, 6–15

show_mop_counter command, *SVCE*, 256

show_status command, *TECH*, D–93;
 SVCE, 196

SIDL, *TECH*, 18–15

SIEN, *TECH*, 18–9

SIER, *TECH*, 4–17
 and corresponding SIRR bits, *TECH*,
 4–15

Single-node system, *OWNR*, 6–2

SIRR, *TECH*, 4–15

Site preparation
 See the *DEC 4000 Site Preparation
 Checklist*

sleep command, *TECH*, D–94

SL_CLR, *TECH*, 4–9

SL_RCV, *TECH*, 4–10

SL_XMIT, *TECH*, 4–18

Snooping protocol, *TECH*, 1–29, 19–4

SOCL, *TECH*, 18–13

SODL, *TECH*, 18–13

Soft errors
 defined, *TECH*, 1–31

Software interrupt enable register, *TECH*,
 4–17

Software interrupt request register, *TECH*, 4-15

Software restart, *OWNR*, 4-5

Software screens, *OWNR*, 1-16

Software shutdown, *OWNR*, 1-17

sort command, *TECH*, D-95

sp command, *TECH*, D-96

SSTAT0, *TECH*, 18-19

SSTAT1, *TECH*, 18-21

SSTAT2, *TECH*, 18-22

Stall signals, *TECH*, 19-21

Standalone system, *OWNR*, 6-2

start command, *TECH*, D-97

Start LBN, *TECH*, 23-5

Startup

- 87C652, *TECH*, 21-6

Startup action, setting, *OWNR*, 4-6

Startup procedure, *OWNR*, 1-12

- See also Power-up procedure

Startup screen, *OWNR*, 1-16

Startup status, *OWNR*, 1-11

Status LEDs, *TECH*, 1-10

stop command, *TECH*, D-98

Stopping a process

- using the kill command (example), *TECH*, 25-13

Storage

- removal and replacement, *SVCE*, 499

Storage, fixed-media

- removal and replacement, *SVCE*, 488

Storage and retrieval system (STARS), *SVCE*, 58

Storage backplane, *TECH*, 1-11

Storage device LEDs, *SVCE*, 90

Storage device local programs, *SVCE*, 292

Storage subsystem, *OWNR*, 7-10

STQC cycle, *TECH*, 7-2

STxC cycle, *TECH*, 7-2

STxC transaction, *TECH*, 7-6

Subsystems, DEC 4000 AXP, *OWNR*, 7-4

sw command, *TECH*, D-99

Switches

- DC on/off, *TECH*, 1-8
- halt, *TECH*, 1-9
- power-up baud rate, *TECH*, 1-9

Switches (cont'd)

- reset, *TECH*, 1-8

SXFER, *TECH*, 18-10

Symmetric multiprocessing, *OWNR*, 6-4

SYSTEST logical name, *SVCE*, 352

System

- characteristics, *OWNR*, 7-2
- configuration, examining, *SVCE*, 612
- expanders, *SVCE*, 609
- functional description, *SVCE*, 548
- installation, *SVCE*, 31
- LEDs, interpreting, *SVCE*, 62
- logging in to for UETP, *SVCE*, 309
- moving, *OWNR*, 8-6
- resource requirements for UETP, *SVCE*, 309
- troubleshooting categories, *SVCE*, 14

System architecture

- design, *OWNR*, 7-4
- overview, *OWNR*, 7-2

System backplane, *TECH*, 1-13; *SVCE*, 554

System block diagram, *SVCE*, 550

System bus, *TECH*, 1-29, 19-1; *OWNR*, 7-4; *SVCE*, 559

- arbiter, *TECH*, 6-22, 19-2
- arbitration, *TECH*, 1-30
- clock, *TECH*, 1-21
- CRESET L generation, *TECH*, 6-22
- cycles, *TECH*, 5-17
- cycle time, *TECH*, 19-6
- idle cycles, *TECH*, 1-30
- interface, *TECH*, 1-21
- interface chip, *TECH*, 6-1
 - initialization, *TECH*, 11-3
- routing, *TECH*, 1-13
- signals, *TECH*, 19-6, 19-7
- supported transactions, *TECH*, 1-29
- test, *TECH*, 26-14
- transaction cycle, *SVCE*, 386
- transactions, *TECH*, 19-1, 19-2
- transaction types, *SVCE*, 386

System bus address cycle failures

- _CA_NOACK, *SVCE*, 421
- _CA_PAR, *SVCE*, 421

- System bus address cycle failures (cont'd)
 - reported by bus commander, *SVCE*, 421
 - reported by bus responders, *SVCE*, 421
- System bus address map, *TECH*, 13-1
- System bus control register, *TECH*, 6-1
- System bus error address high register, *TECH*, 6-11
- System bus error address low register, *TECH*, 6-10
- System bus error register, *TECH*, 6-4
- System bus stall, *TECH*, 13-28
- System bus transactions, *TECH*, 7-1
 - CPU as bystander, *TECH*, 7-10
 - CPU as commander, *TECH*, 7-10
 - null, *TECH*, 1-30
- System bus transactions, *TECH*, 7-9
 - CPU as responder, *TECH*, 7-10
 - reasons for monitoring, *TECH*, 7-1
- System bus write-data cycle failures
 - reported by commander, *SVCE*, 429
 - reported by responders, *SVCE*, 429
 - _WD_NOACK, *SVCE*, 429
 - _WD_PAR, *SVCE*, 429
- System components
 - front, *OWNR*, 1-5
 - rear, *OWNR*, 1-7
- System configuration, *OWNR*, 6-2
 - See Configuration
 - adding third-party devices, *OWNR*, 6-17
 - additional documentation about, *OWNR*, 6-33
 - displaying in console mode, *OWNR*, 6-10
 - planning, *OWNR*, 6-16
- System disk space and UETP, *SVCE*, 316
- System doors, removing, *OWNR*, 8-4
- System enclosure, warning symbols, *SVCE*, 480
- System event
 - causes, *TECH*, 1-31
- System event interrupts, *TECH*, 14-3
- System expansion, *SVCE*, 608
- System faults
 - interpreting with ERF, *SVCE*, 411
 - interpreting with UERF, *SVCE*, 411
- System features, *TECH*, 1-1
- System features summary, *TECH*, 1-3
- System hang, *SVCE*, 359
- System I/O, *TECH*, 1-2
- System I/O space, *TECH*, 13-2
- SYSTEMID parameter, *OWNR*, 6-27; *SVCE*, 673
- System initialization, *TECH*, 21-6
- System interrupt clear register, *TECH*, 6-14
- System keys, locating, *OWNR*, 1-2
- System maintenance, *OWNR*, 8-9
- System memory space, *TECH*, 13-1
- System modules, *OWNR*, 6-6
- System operation
 - actions before power-up, *OWNR*, 1-11
 - boot, *OWNR*, 1-15
 - halt, *OWNR*, 1-18
 - overview, *OWNR*, 1-10
 - power-down, *OWNR*, 1-21
 - power-up, *OWNR*, 1-12
 - reboot, *OWNR*, 1-15
 - reset, *OWNR*, 1-20
- System power down, *OWNR*, 1-21
- System power-up
 - actions before beginning, *OWNR*, 1-11
 - procedure, *OWNR*, 1-12
 - task overview, *OWNR*, 1-11
- System power-up screen, *OWNR*, 1-13
- System setting, time and date, *OWNR*, 3-11
- System software
 - booting, *OWNR*, 1-15
 - shutdown, *OWNR*, 1-17
- System startup status, determining, *OWNR*, 1-11
- SYSTEST account
 - logging in to for UETP, *SVCE*, 309
- SYSTEST directory
 - creating for UETP, *SVCE*, 321
- S_floating, *TECH*, 3-6

T

Tag store, *TECH*, 5-2

Tape booting, *TECH*, 23-6

Tape cartridge drive

preparing for UETP, *SVCE*, 327

Tape device local programs, *SVCE*, 292

Tape drive media, labeling, *OWNR*, 5-38

Tape drives

See also specific drives

handling and storing, *OWNR*, 5-39

mounting, *OWNR*, 5-2

TLZ06, *OWNR*, 5-16

TZ30, *OWNR*, 5-29

TZ85, *OWNR*, 5-22

Tapes

See CompacTape cartridges;

CompacTape II

cartridges; CompacTape III

cartridges; Tape drive media

TB_CTL, *TECH*, 4-19

TB_TAG, *TECH*, 4-2

TDES0 word, *TECH*, 17-34

TDES1 word, *TECH*, 17-35

TDES2 word, *TECH*, 17-37

TDES3 word, *TECH*, 17-37

Technical Information Management

Architecture (TIMA), *SVCE*, 52

Technical updates, *SVCE*, 57

TEMP, *TECH*, 18-33

Terminal, preparing for UETP, *SVCE*, 310, 334

test command, *TECH*, D-100; *OWNR*, 3-24; *SVCE*, 177

Testing

See also Commands; Loopback tests

acceptance, *SVCE*, 361

commands to perform extended exercising, *SVCE*, 174

command summary, *SVCE*, 282

memory, *SVCE*, 214, 220

with DEC VET, *SVCE*, 299

with DSSI device internal tests, *SVCE*, 284

Testing (cont'd)

with UETP, *SVCE*, 303

Test procedure

monitoring self-test, *OWNR*, 1-21

sample self-test screen, *OWNR*, 1-13

TGEC, *TECH*, 17-1

See Ethernet controllers

virtual to physical address translation, *TECH*, 17-28

TGEC command and status registers, *TECH*, 17-3

TGEC CSR0, *TECH*, 17-5

TGEC CSR1, *TECH*, 17-7

TGEC CSR10, *TECH*, 17-25

TGEC CSR11, *TECH*, 17-26

TGEC CSR12, *TECH*, 17-26

TGEC CSR13, *TECH*, 17-26

TGEC CSR14, *TECH*, 17-28

TGEC CSR15, *TECH*, 17-28

TGEC CSR2, *TECH*, 17-8

TGEC CSR3, *TECH*, 17-9

TGEC CSR4, *TECH*, 17-9

TGEC CSR5, *TECH*, 17-12

TGEC CSR5 and interrupts, *TECH*, 17-45

TGEC CSR5 status report, *TECH*, 17-15

TGEC CSR6, *TECH*, 17-17

TGEC CSR7, *TECH*, 17-22

TGEC CSR8, *TECH*, 17-23

TGEC CSR9, *TECH*, 17-23

TGEC CSR read, *TECH*, 17-4

TGEC CSR write, *TECH*, 17-4

TGEC loopback, *TECH*, 17-50

TGEC physical CSRs, *TECH*, 17-4

TGEC programming, *TECH*, 17-2

TGEC reception process, *TECH*, 17-46

TGEC register map, *TECH*, 17-1

TGEC reset, *TECH*, 17-44

TGEC setup frame, *TECH*, 17-38

TGEC startup procedure, *TECH*, 17-46

TGEC states, *TECH*, 17-2

TGEC transmission process, *TECH*, 17-48

TGEC transmit descriptors, *TECH*, 17-33

TGEC virtual CSRs, *TECH*, 17-4

- Third-party devices, adding, *OWNR*, 6–17
- TIMA, *SVCE*, 52
- Time, displaying and modifying, *OWNR*, 3–11
- Time domains, *TECH*, 1–33
- Time-of-year clock, *TECH*, 16–6
- TLZ06 drive
 - supported by UETP, *SVCE*, 330
- TLZ06 drives
 - cleaning, *OWNR*, 5–40
 - compatible tapes, *OWNR*, 5–16
 - components, *OWNR*, 5–16
 - described, *OWNR*, 5–16
 - hardware specifications, *OWNR*, 5–4
 - inserting a tape into, *OWNR*, 5–18
 - lights (table), *OWNR*, 5–20
 - operating, *OWNR*, 5–16
 - removing a tape from, *OWNR*, 5–18
 - tapes, labeling, *OWNR*, 5–38
- Tools, *SVCE*, 33
 - See also Service
 - console commands, *SVCE*, 36
 - crash dumps, *SVCE*, 47
 - DEC VET, *SVCE*, 45
 - error handling, *SVCE*, 34
 - log files, *SVCE*, 34
 - loopback tests, *SVCE*, 39
 - maintenance strategy, *SVCE*, 33
 - option LEDs, *SVCE*, 43
 - RBDs, *SVCE*, 36
 - UETP, *SVCE*, 45
- TOYA, *TECH*, 16–7
- TOYB, *TECH*, 16–9
- TOYC, *TECH*, 16–11
- TOY clock, *TECH*, 16–6
- TOYD, *TECH*, 16–12
- TOY registers, *TECH*, 1–46
- Training courses, *SVCE*, 54
- TRANS<2:0>, *TECH*, 19–12
- Transaction counter, *TECH*, 1–30
- Transactions
 - CPU module, *TECH*, 7–1
 - memory exchange, *TECH*, 19–26
 - memory write, *TECH*, 19–28
- Transactions (cont'd)
 - noncacheable address space write, *TECH*, 19–30
 - null, *TECH*, 19–24
 - read and read exclusive, *TECH*, 19–20
- Transactions
 - processor initiated, *TECH*, 7–2
- Transaction timing, *TECH*, 19–19
- Translation buffer control register, *TECH*, 4–19
- Transmit descriptor status validity, *TECH*, 17–37
- tr command, *TECH*, D–102
- Troubleshooting
 - See also Diagnostics; Service
 - actions before beginning, *SVCE*, 11
 - boot problems, *SVCE*, 25
 - categories of system problems, *SVCE*, 14
 - console, *SVCE*, 23
 - crash dumps, *SVCE*, 47
 - diagnostic tools, *SVCE*, 18
 - error report formatter, *SVCE*, 34
 - errors reported by operating system, *SVCE*, 26
 - interpreting LEDs, *SVCE*, 64, 95
 - interpreting UETP failures, *SVCE*, 347
 - mass storage problems, *SVCE*, 104
 - option LEDs, *SVCE*, 43
 - power problems, *SVCE*, 21
 - problems reported by the console, *SVCE*, 24
 - procedures, *SVCE*, 17
 - UETP, *SVCE*, 357
 - with DEC VET, *SVCE*, 45
 - with loopback tests, *SVCE*, 39
 - with operating system exercisers, *SVCE*, 45
 - with ROM-based diagnostics, *SVCE*, 36
 - with UETP, *SVCE*, 45
- TSZ07 drives
 - finding information on, *OWNR*, 5–42
 - hardware specifications, *OWNR*, 5–4
- tta0_baud environment variable
 - described, *OWNR*, 4–2
 - displaying current value, *OWNR*, 4–16

tta0_halts environment variable
 described, *OWNR*, 4-2
 tta1_baud environment variable
 described, *OWNR*, 4-2
 displaying current value, *OWNR*, 4-16
 tta1_halts environment variable
 described, *OWNR*, 4-2
 two-conductor interconnect, *TECH*, 1-43
 TZ30 drives
 cleaning, *OWNR*, 5-41
 compatible tapes, *OWNR*, 5-29
 components, *OWNR*, 5-29
 described, *OWNR*, 5-29
 hardware specifications, *OWNR*, 5-4
 inserting a tape into, *OWNR*, 5-32
 lights, *OWNR*, 5-36
 operating, *OWNR*, 5-29
 removing a tape from, *OWNR*, 5-34
 tapes, labeling, *OWNR*, 5-38
 TZ85 drives
 cleaning, *OWNR*, 5-41
 compatible tapes, *OWNR*, 5-22
 components, *OWNR*, 5-22
 described, *OWNR*, 5-22
 hardware specifications, *OWNR*, 5-4
 inserting a tape into, *OWNR*, 5-24
 lights, *OWNR*, 5-28
 operating, *OWNR*, 5-22
 removing a tape from, *OWNR*, 5-26
 tapes, labeling, *OWNR*, 5-38
 T_floating, *TECH*, 3-7

U

UERF
 interpreting system faults with, *SVCE*, 411
 UERF-generated error log, sample of, *SVCE*, 473
 UETINIT01.EXE image, *SVCE*, 359
 UETP
 aborting execution of, *SVCE*, 346
 DECnet for OpenVMS AXP, *SVCE*, 339
 described, *SVCE*, 303
 errors, *SVCE*, 357

UETP (cont'd)

 interpreting OpenVMS AXP failures with, *SVCE*, 347
 interpreting output of, *SVCE*, 350
 log files, *SVCE*, 352
 operating instructions, *SVCE*, 308
 operating system exerciser, *SVCE*, 303
 preparing additional disks for, *SVCE*, 318
 preparing disk drives for, *SVCE*, 318
 running all phases of, *SVCE*, 310
 running multiple passes of, *SVCE*, 352
 running on RRD42 compact disc drives, *SVCE*, 333
 setting up tape cartridge drives for, *SVCE*, 327
 setting up tape drives for, *SVCE*, 324
 set-up, *SVCE*, 303
 system disk, space required for, *SVCE*, 316
 termination of, *SVCE*, 344
 testing Ethernet adapters with, *SVCE*, 337
 testing terminals and line printers with, *SVCE*, 334
 TLZ06 tape drive time limit, *SVCE*, 330
 typical failures reported by, *SVCE*, 358
 User Identification Code (UIC), *SVCE*, 322
 UETP\$NODE_ADDRESS logical name, *SVCE*, 339
 UETP.COM file, termination of, *SVCE*, 344
 UETP.LOG file, *SVCE*, 352
 Uninterruptible power supply
 See UPS
 uniq command, *TECH*, D-103
 UNITNUM parameter, *OWNR*, 6-27; *SVCE*, 670
 update, *TECH*, D-104
 UPS, *OWNR*, 7-9
 Use Cleaning Tape light, *OWNR*, 5-41
 User disk, preparing for UETP, *SVCE*, 309, 318, 323

User Environment Test Package

See UETP

Using pipes (|) and grep

to filter output, *TECH*, 25–10

Using quotes

to write longer scripts, *TECH*, 25–14

Write-protecting

defined, *OWNR*, 5–37

RZ- or RF-series drive, *OWNR*, 5–8

WRITE_BLOCK cycle, *TECH*, 7–1

WRITE_BLOCK transaction, *TECH*, 7–5

V

VA, *TECH*, 4–22

VAX architecture, *OWNR*, 7–3

VAX compatibility registers, *TECH*, 3–12

VAX console commands, *OWNR*, 3–3

VERIFY local program, *SVCE*, 293

Virtual address register, *TECH*, 4–22

Virtual cache, *TECH*, 8–1

VMS

See OpenVMS AXP operating system

VMScluster configurations, *OWNR*, 6–4

VMS operating system, *OWNR*, 7–3

See also OpenVMS AXP operating system

Voltages, *TECH*, 1–42

+24 and -24 VDC, *TECH*, 1–41

disk power source, *TECH*, 1–34

VT420 terminal, keyboard characters,

OWNR, 2–6

Vterm module

removal and replacement, *SVCE*, 485

W

Warm bootstrap, *SVCE*, 158

Warning symbols, *SVCE*, 480

wc command, *TECH*, D–106

Word, *TECH*, 3–1

Word tearing, *TECH*, 5–17

Wrist strap, using, *OWNR*, 8–6

Write

to non-cacheable addresses, *TECH*, 7–7

to secondary bus, *TECH*, 13–37

Write-enabling

defined, *OWNR*, 5–37

RZ- or RF-series drive, *OWNR*, 5–8