Software Product Description

PRODUCT NAME: PDP-11 FORTRAN-77/RSTS/E, Version 5.4

SPD 14.49.14

DESCRIPTION

PDP-11 FORTRAN-77/RSTS/E is an extended implementation of the ANSI subset FORTRAN-77 standard (X3.9-1978) that runs on the RSTS/E Operating System. PDP-11 FORTRAN-77/RSTS/E contains all the features of ANSI FORTRAN-77 subset, many of the full-set language features, and extensions that are not included in the ANSI FORTRAN-77 standard. Switch-selectable support is provided for user programs conforming to the previous ANSI FORTRAN standard (X3.9-1966).

PDP-11 FORTRAN-77/RSTS/E also meets the Federal Information Processing Standard Publication (FIPS PUB-69) requirement for a flagger. The flagger optionally produces diagnostic messages for syntax and/or source form elements which do not conform to the full-level ANSI FORTRAN X3.9-1978 Standard.

PDP-11 FORTRAN-77/RSTS/E programs can be optionally executed under the control of PDP-11 Symbolic Debugger/RSTS/E (SPD 12.79.xx). Execution of application programs using PDP-11 Symbolic Debugger/RSTS/E aids in the location of programming errors in successfully compiled programs that behave abnormally when executed.

PDP-11 FORTRAN-77/RSTS/E includes all subset ANSI features including:

- CHARACTER data type
- Block IF construct, including IF...THEN, ELSE IF, ELSE, and END IF statements, for conditional execution of blocks of statements

The PDP-11 FORTRAN-77/RSTS/E compiler includes the following features of full-language FORTRAN as defined by the ANSI Standard:

- · Double precision and complex data types
- · Intrinsic functions, including LEN, ICHAR, and INDEX
- Exponentiation forms, including double precision and complex
- Format edit descriptors, including S, SP, SS, T, TL, TR, lw.m, and Gw.dEe
- Generalized DO loop parameters
- · DO WHILE and END DO logic statements
- Generic function selection based on argument data type for FORTRAN-defined functions

- Lower and upper bounds specification in array declarators
- Substrings of character variables and character array elements
- Optional syntax for I/O statements (UNIT= and FMT=)
- Support for real and complex constant expressions in PARAMETER statement
- · IMPLICIT NONE statement

PDP-11 FORTRAN-77/RSTS/E includes the following extensions to the ANSI standard:

- Language elements for keyed and sequential access to RMS multi-key ISAM files
- DEFINE FILE, FIND, DELETE, REWRITE, and UNLOCK statements
- TYPE and ACCEPT input/output statements
- · Comments permitted at the end of each source line
- · INCLUDE statement
- BYTE data type
- ENCODE, DECODE statements
- Explicit specification of storage allocation units for data types (e.g., INTEGER*4)
- · Hexadecimal and octal constants
- User mode instruction and data space (I & D space) support on processors where both the hardware and software support this feature
- O and Z format edit descriptors

The PDP-11 FORTRAN-77 compiler performs optimization on source code to improve execution-time efficiency on a PDP-11 with a floating point processor. PDP-11 FORTRAN-77 compiler optimizations include:

- · Optimizations of arithmetic and logical IF statements
- Common subexpression elimination
- Removal of invariant expressions from DO loops
- Allocation of processor registers across block IF constructs and DO loops



Object Time System

The PDP-11 FORTRAN-77/RSTS/E Object Time System (OTS) is a set of object modules that are selectively linked with compiler-produced object modules by the operating system's task builder, to produce a task (program) ready for execution.

PDP-11 FORTRAN-77/RSTS/E provides the capability of creating either or both of the following Object Time systems:

- The OTS based on File Control Services (FCS) allows sequential and random access to sequentially organized files.
- The OTS based on Record Management Services (RMS) uses RMS to provide access to sequential, relative, and indexed organizational files.

The RMS OTS is normally larger than the FCS OTS, but provides additional capabilities. For a given task, it is not possible to mix FCS OTS modules with RMS OTS modules.

HARDWARE REQUIREMENTS

Any valid RSTS/E Operating System configuration with:

- Floating Point Processor (FPP)
- At least 56K bytes of user memory

Block Space Requirements:

Disk Space required for installation:

2,270 Blocks (1.2M bytes)

These counts refer to the disk space required on the System Disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options selected.

Note: Within this disk space requirement, there must be 400 contiguous blocks for the compiler and 160 contiguous blocks for each OTS library.

Note: The FPP is not required if the user's source program does not exercise floating point arithmetic.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements of the current version.

OPTIONAL HARDWARE

None

SOFTWARE REQUIREMENTS

RSTS/E Operating System

Refer to RSTS/E Optional Software Cross Reference Table (SPD 20.97.xx) for the required version.

OPTIONAL SOFTWARE

PDP-11 Symbolic Debugger/RSTS/E

SOFTWARE LICENSING

This software is furnished under the provisions of Digital Equipment Corporation's Stadard Terms and Conditions. For more information about Digitals licensing terms and policies, contact your local Digital office.

SOFTWARE PRODUCT SERVICES

A variety of service options are available. For more information, please contact your local Digital office.

SOFTWARE WARRANTY

Warranty for this software product is provided by Digital with the purchase of a license for the product as defined in the Software Warranty Addendum of this SPD.

Note: The software being licensed is warranted only if the hardware configuration on which the software is to be run is a configuration explicitly supported by the RSTS/E Operating System (refer to SPD 13.01.xx).

SOFTWARE OPTIONS CHART

The distribution Media Codes used in the Software Options Chart are described below. You specify the desired Media Code at the end of the Order Number, e.g., QR100-HD = binaries on 9-track 800 BPI Magtape (NRZI).

5 = TK50 Tape Cartridge D = 9 track 800 BPI Magtape

H = RL02 Disk Cartridge

M = 9-track 1600 BPI Magtape (PE)

V = RK07 Disk Cartridge

Z = No hardware dependency

Note: The availability of these software product options and services may vary by country. Customers should contact their local Digital office for information on availability.

OPTIONS	ORDER NUMBER CLASS L SYSTEMS ¹	ORDER NUMBER CLASS H SYSTEMS ²
LICENSE OPTIONS: A LICENSE IS REQUIRED FOR EACH CPU.		
Single-Use License	QY100-UZ	QR100-UZ
Migration Option from PDP-11 FORTRAN IV/RSTS/E	QY453-UZ	QR453-UZ
MATERIALS AND SERVICE OPTIONS:		
Distribution and Documentation Option	QY100-H5 QY100-HH QY100-HM	QR100-H5 QR100-HD QR100-HH QR100-HM QR100-HV
Software Revision Right-To-Copy Option	QY100-HZ	QR100-HZ
Documentation-Only Option	QY100-GZ	QR100-GZ
Installation Service Option	QY100-I5 QY100-IH QY100-IM	QR100-I5 QR100-ID QR100-IH QR100-IM QR100-IV
DECsupport Service	QY100-95 QY100-9H QY100-9M	QR100-95 QR100-9D QR100-9H QR100-9M QR100-9V

SOFTWARE OPTIONS CHART (cont'd)

OPTIONS	ORDER NUMBER CLASS L SYSTEMS ¹	ORDER NUMBER CLASS H SYSTEMS ²
Basic Service	QY100-85 QY100-8H QY100-8M	QR100-85 QR100-8D QR100-8H QR100-8M QR100-8V
Self-Maintenance Service	QY100-35 QY100-3H QY100-3M	QR100-35 QR100-3D QR100-3H QR100-3M QR100-3V

¹ Class L Systems (low-end systems):

- All Q-bus models and systems including MicroPDP-11/83 KD11, KDF11, KDJ11 CPU modules DCT11, DCF11, DCJ11 microprocessor chips

All UNIBUS models and systems

² Class H Systems (high-end systems):

[®] The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

[™] VAX, VMS, MicroVAX, VAXstation, VAXserver, VAXcluster, RSTS, RSTS/E, PDP-11, TK50, RL02, RK07, Q-bus and UNIBUS are trademarks of Digital Equipment Corporation.