

# Reflection

see Sun's tutorial

# Reflection API

- allows fully dynamic access to internal stuff
  - actual class of an object
  - all kind of info about a class
  - as well as interfaces
  - create instances without knowing the class at compile time
  - get and set field values (without ...)
  - invoke methods (without ...)
  - create and manipulate arrays (without ...)

# Retrieving Class Objects

- `Class c = x.getClass();`
- `Class s = c.getSuperClass();`
- `Class t = java.awt.Button.class;`
- `Class u = Class.forName("java.awt.Button");`

# Inspecting Classes

```
static void printClassName(Object o) {  
    Class c = o.getClass();  
    String s = c.getName();  
    System.out.println(s);  
}  
  
static void printModifiers(Object o) {  
    int m = o.getClass().getModifiers();  
    if (Modifier.isPublic(m)) ...  
}
```

# All superclasses

```
static List allSuperClasses(Object o) {  
    List superClasses = new ArrayList();  
    Class subClass = o.getClass();  
    Class superClass = subClass.getSuperClass();  
    while (superClass != null) {  
        superClasses.add(superClass);  
        subClass = superClass;  
        superClass = subClass.getSuperClass();  
    }  
    return superClasses;  
}
```

# All SuperClasses (recursive)

```
static List allSuperClasses(Object o) {  
    return allSuperClasses(o.getClass().getSuperClass(),  
        new ArrayList());  
}
```

```
static List allSuperClasses(Class c, List all) {  
    if (c == null) return all;  
    all.add(c);  
    return allSuperClasses(c.getSuperClass(), all);  
}
```

# Interfaces

Interfaces are represented by class Class as well

```
Class[] myInterfaces = o.getClass().getInterfaces();
```

i.e. there is no separate class for Interfaces, but a test:  
`isInterface();`

can use `getFields()` and `getMethods()` like with classes

# Retrieving field info

```
static void printFieldNames(Object o)
{
    Field[] publicFields = o.getClass().getFields();
    for(int i = 0; i<publicFields.length; i++) {
        String fieldName = publicFields[i].getName();
        Class typeClass = publicFields[i].getType();
        String typeName = typeClass.getName();
        System.out.println("Name: " + fieldName + ", Type: " +
                           typeName);
    }
}
```



# Constructors

```
Constructor[] cons = c.getConstructors();  
for(int i = 0; i<cons.length; i++) {  
    Class[] paramTypes = cons[i].getParameterTypes();  
    ...  
}  
also:  
for(int i = 0; i<cons.length; i++) {  
    Class[] exTypes = cons[i].getExceptionTypes();  
    ...  
}
```

# Methods

```
Method[] methods = c.getMethods();
for(int i = 0; i<methods.length; i++) {
    String name = methods[i].getName();
    Class returnType = methods[i].getReturnType();
    Class[] paramTypes = methods[i].getParameterTypes();
    Class[] exTypes = methods[i].getExceptionTypes();
    int modifiers = methods[i].getModifiers();
    ...
}
```